

G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Material number : 0000000001002639

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW

Atlanta, GA 30318

Telephone : 404-352-1680

Emergency	, telephone	numbers
EIIIOI GOIIO	,	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

For SDS Information : Compliance Services 1-877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded
For a Transportation : CHEMTREC: 800-424-9300 - All Calls Recorded.

Emergency In the District of Columbia 202-483-7616

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	clear, colourless
Odour	oily

GHS Classification

Flammable liquids : Category 3
Skin irritation : Category 2
Serious eye damage : Category 1
Germ cell mutagenicity : Category 1B
Carcinogenicity : Category 2
Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :





Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage. H340 May cause genetic defects. H351 Suspected of causing cancer.

Precautionary statements : **Prevention:**



Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4 naphthalene 91-20-3 cumene 98-82-8

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethylbenzene 100-41-4 cyclohexanone 108-94-1

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Reasonably anticipated to be a human carcinogen

naphthalene 91-20-3



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 70 - < 90
2-ethylhexyl nitrate	27247-96-7	>= 5 - < 10
xylenes	1330-20-7	>= 5 - < 10
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 1 - < 5
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 1 - < 5
ethylbenzene	100-41-4	>= 1 - < 5
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 5
cyclohexanone	108-94-1	>= 1 - < 5
naphthalene	91-20-3	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Carbon dioxide (CO2)

Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage : Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : Oxidizing agents

Do not freeze.



Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters /	Basis
		exposure)	Permissible concentration	
xylenes	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm	ACGIH
		STEL	125 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m3	NIOSH REL
cyclohexanone	108-94-1	TWA	20 ppm	ACGIH
		STEL	50 ppm	ACGIH
		TWA	25 ppm 100 mg/m3	NIOSH REL
		TWA	50 ppm 200 mg/m3	OSHA Z-1
		TWA	25 ppm 100 mg/m3	OSHA P0
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm 50 mg/m3	OSHA P0
		STEL	15 ppm 75 mg/m3	OSHA P0
cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA P0

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

ETHYLENZENE	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of workwee k	700 mg/g	ACGIH BEI
Remarks: Creatinine						
ETHYLENZENE		Ethylbenzen e	In end- exhaled air	Not critical		ACGIH BEI
CYCLOHEXANONE	108-94-1	1,2- Cyclohexan ediol	Urine	End of shift at end of workwee k	80 mg/l	ACGIH BEI
CYCLOHEXANONE		Cyclohexan ol	Urine	End of shift (As soon as possible after exposure ceases)	8 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless

Odour : oily



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

Odour Threshold : no data available

no data available

pН : not applicable

Melting point/freezing point : no data available

Boiling point 132 °C Flash point 47.2 °C

Method: TCC

Evaporation rate : > 10

Upper explosion limit : no data available Lower explosion limit : no data available Vapour pressure : no data available Relative vapour density : no data available

no data available

: 0.833 g/cm3 Density

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: no data available

no data available Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

: 6.0 mm2/s (20.0 °C) Viscosity, kinematic

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials Strong oxidizing agents

Hazardous decomposition

products

Carbon monoxide, carbon dioxide and unburned

hydrocarbons (smoke).



Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light:

2-ethylhexyl nitrate:

xylenes:

Solvent naphtha (petroleum), light arom.:

Solvent naphtha (petroleum), heavy arom.:

ethylbenzene:

1,2,4-trimethylbenzene:

cyclohexanone:

naphthalene:

STOT - single exposure

no data available



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

Remarks: no data available

Remarks: Solvents may degrease the skin.

Components:

Distillates (petroleum), hydrotreated light:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n- : Remarks: no data available

octanol/water

Remarks: no data available

Components:

xylenes:

Partition coefficient: n- : Pow: 3.12

octanol/water

Solvent naphtha (petroleum), heavy arom. : Partition coefficient: n- : log Pow: 4.2

octanol/water ethylbenzene:

Partition coefficient: n- : Pow: 3.6

octanol/water cyclohexanone:

Partition coefficient: n- : log Pow: 0.81

octanol/water

Mobility in soil

no data available

Other adverse effects



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

> with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: no data available

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

no data available

Components:

Distillates (petroleum), hydrotreated light :

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International regulation

IATA-DGR

UN/ID No. : 1993

Proper shipping name : Flammable liquid, n.o.s.

(HYDROTREATED LIGHT PETROLEUM DISTILLATES)

: 3 Class Packing group III : 3 Labels Packing instruction (cargo

aircraft)

: 366



G00421 Mst Cf5d Dsl Fuel Adtv 6gll

Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

Packing instruction : 355

(passenger aircraft)

IMDG-Code

UN number : 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

(HYDROTREATED LIGHT PETROLEUM DISTILLATES)

 Class
 : 3

 Packing group
 : III

 Labels
 : 3

 EmS Code
 : F-E, S-E

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : 1993

Proper shipping name : Flammable liquids, n.o.s.

(HYDROTREATED LIGHT PETROLEUM DISTILLATES)

Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

Special precautions for user

not applicable

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
xylenes	1330-20-7	100	1346

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard



Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313: ethylbenzene 100-41-4 1,2,4-trimethylbenzene 95-63-6 naphthalene 91-20-3

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

ethylbenzene 100-41-4 naphthalene 91-20-3 cumene 98-82-8

The components of this product are reported in the following inventories:

All components of this product are on the Canadian DSL.

On the inventory, or in compliance with the inventory

NZIoC Not in compliance with the inventory

PICCS On the inventory, or in compliance with the inventory IECSC On the inventory, or in compliance with the inventory


Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:



Version 1.0 Revision Date 01/09/2015 Print Date 06/01/2015

Hazard pictograms







Signal word :

Hazard statements : Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes

skin irritation. Causes serious eye damage. May cause genetic defects. Suspected of

causing cancer.

Danger:

Precautionary statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection. Use personal protective equipment as required.

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/ attention. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up. **Disposal:** Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.