

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00314 MST MULTIPURPOSE ADHSV 20net12

Material number : 000000000001002026

Manufacturer or supplier's details

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW
Atlanta, GA 30318

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesive

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	light yellow
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1
 Gases under pressure : Liquefied gas
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Reproductive toxicity : Category 2
 Specific target organ toxicity - single exposure : Category 2
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
 H280 Contains gas under pressure; may explode if heated.
 H315 Causes skin irritation.

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361 Suspected of damaging fertility or the unborn child.
 H371 May cause damage to organs.

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 20 - < 30
propane	74-98-6	>= 10 - < 20

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

butane	106-97-8	>= 10 - < 20
n-hexane	110-54-3	>= 5 - < 10
Mixture of hexanes	Not Assigned	>= 5 - < 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
methyl acetate	79-20-9	>= 1 - < 5
methylcyclopentane	Methylcyclopentane	>= 1 - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Get medical attention if irritation develops and persists.
Wash contaminated clothing before re-use.
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.
Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Keep respiratory tract clear.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Effects are dependent on exposure (dose, concentration, contact time).
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	: For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place.

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
		STEL	750 ppm 1,780 mg/m ³	CAL PEL
		C	3,000 ppm	CAL PEL
propane	74-98-6	PEL	500 ppm 1,200 mg/m ³	CAL PEL
		TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0
		PEL	1,000 ppm 1,800 mg/m ³	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	NIOSH REL
		TWA	800 ppm 1,900 mg/m ³	OSHA P0
		PEL	800 ppm 1,900 mg/m ³	CAL PEL
n-hexane	110-54-3	TWA	50 ppm	ACGIH
		TWA	50 ppm 180 mg/m ³	NIOSH REL
		TWA	500 ppm 1,800 mg/m ³	OSHA Z-1
		TWA	50 ppm 180 mg/m ³	OSHA P0
		PEL	50 ppm 180 mg/m ³	CAL PEL
methyl acetate	79-20-9	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 610 mg/m ³	NIOSH REL
		ST	250 ppm	NIOSH REL

SAFETY DATA SHEET



A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

			760 mg/m3	
		TWA	200 ppm 610 mg/m3	OSHA Z-1
		TWA	200 ppm 610 mg/m3	OSHA P0
		STEL	250 ppm 760 mg/m3	OSHA P0
		PEL	200 ppm 610 mg/m3	CAL PEL
		STEL	250 ppm 760 mg/m3	CAL PEL

Hazardous components without workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
HEXANE	110-54-3	2,5-Hexanedione	Urine	End of shift at end of workweek	0.4 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection
Remarks

: Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety glasses
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Appearance	: Aerosol containing a liquefied gas
Colour	: light yellow
Odour	: solvent-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 40.23 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions. No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Hazardous decomposition products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION
Potential Health Effects

Aggravated Medical Condition : None known.

Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Effects are dependent on exposure (dose, concentration, contact time).

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity
Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:
acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

propane:

SAFETY DATA SHEET



A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 658 mg/l
Exposure time: 4 h

LC50 Rat: 1,355 mg/l

butane:
Acute inhalation toxicity : LC50 Mouse: 1,237 mg/l
Exposure time: 2 h

LC50 Rat: 1,355 mg/l

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

acetone:

propane:

butane:

n-hexane:

Mixture of hexanes:

Naphtha (petroleum), hydrotreated light:

methyl acetate:

methylcyclopentane:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Further information**Product:**Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Components:**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

n-hexane :

Partition coefficient: n-octanol/water : log Pow: 3.9 - 4.11

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**Waste from residues : Dispose of in accordance with local regulations. The product should not be allowed to enter drains, water

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Do not burn, or use a cutting torch on, the empty drum.
Do not re-use empty containers.
Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.
No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET



A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

SARA 311/312 Hazards : Fire Hazard
Sudden Release of Pressure Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
n-hexane 110-54-3 8.4929 %

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.
benzene 71-43-2
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
toluene 108-88-3
benzene 71-43-2

The components of this product are reported in the following inventories:

TSCA Not On TSCA Inventory
DSL This product contains one or several components that are not on the Canadian DSL nor NDSL.

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

A00314 MST MULTIPURPOSE ADHSV 20net12

Version 3.1

Revision Date 01/10/2017

Print Date 04/28/2017

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs.

Precautionary statements

:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Call a POISON CENTER/doctor. IF exposed or concerned: Get medical advice/ attention. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	01/10/2017
Print Date:	04/28/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.