

Safety Data Sheet

Revision Date: 2/26/2015

Section 1: Product and Company Identification

Product Name: Biofreeze Gel and Roll On Colorless

Chemical Family: Mixture

Recommended Use: Topical Pain Reliever

Restrictions on Use: No Data

Company: Performance Health, Inc.

1245 Home Avenue Akron, OH 44310

Telephone: (330) 633-8460 (Only available during normal business hours.)

Email: web@biofreeze.com

Emergency Telephone: (800) 321-2135 **CHEMTREC (Transportation):** (800) 424-9300

U.S. Coast Guard National

Response Center: (800) 424-8802

Section 2: Hazards Identification

Emergency Overview:

Warning: Flammable. May cause eye irritation. May be harmful if swallowed.

GHS Classification:

Flammable Liquid, Category 3 Eye Irritant, Category 2B

GHS Label Elements:

Pictograms:



Signal Word: Warning

Hazard Statements:

H226: Flammable liquid and vapor

Revision Date: 2/26/2015 Page 1 of 10

H318: Causes eye irritation

Precautionary Statements:

P210: Keep away from heat/sparks/open flames/hot surfaces.-No smoking.

P233: Keep container tightly closed.

P264: Wash hands thoroughly after handling.

P403 + P235: Store in a well-ventilated place. Keep cool.

Classification According to Directive 1999/45/EC:

European Economic Community Information: This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

EU Classification: [R10] Flammable, [Xi] Irritant

EU Risk Phrases: R10: Flammable; R36: Irritating to eyes.

EU Safety Phrases: S2: Keep out of reach of children; S7: Keep container tightly closed; S16: Keep away from sources of ignition – No smoking; S25: Avoid contact with eyes; S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

EU Symbols:



Section 3: Composition/Information on Ingredients

Chemical Ingredients:	CAS Number:	EC Number	Index Number	Percent Range:	Classification of Ingredient according to 67/548/EEC*	Classification of Ingredient according to Regulation (EC) No 1272/2008 [CLP]*
Isopropyl Alcohol	67-63-0	200-661-7	603-117-00-0	15 - 40%	F; R11 Xi; R36 R67	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT Single 3 H336
L-Menthol	2216-51-5	218-690-9	Not Available	3 – 7%	Not classified. Substance with a community workplace exposure limit.	
Glycerine	56-81-5	200-289-5	Not Available	1 – 5%	Not classified. Substance with a community workplace exposure limit.	

*Legend: F: Highly flammable

R11: Highly flammable

Xi: Irritant

R36: Irritating to eyes

Revision Date: 2/26/2015

R67: Vapors may cause drowsiness or dizziness

H225: Highly flammable liquid and vapor H319: Causes serious eve irritation

H336: May cause drowsiness or dizziness

Section 4: First Aid Measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if victim feels unwell.

Skin Contact: Not applicable.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

Section 5: Fire Fighting Measures

Suitable Extinguishing Media: Water, carbon dioxide, dry chemical, or foam

Specific Hazards in Case of Fire: None known.

Special Protective Equipment for Fire-Fighters: Use protective clothing and breathing equipment appropriate for the surrounding fire.

Section 6: Accidental Release Measures

Personal Precautions: Eliminate all ignition sources and heat sources if safe to do so. Take off contaminated clothing and wash before reuse.

Environmental Precautions: Do not flush into surface water or sanitary sewer system.

Methods for Containment/Cleaning Up: Contain spillage and collect with non-combustible absorbent material. Disposal should be in accordance with all applicable local, state and federal regulations.

Section 7: Handling and Storage

Handling: Avoid breathing vapor or mist. Wash hands thoroughly after handling. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Keep out of reach of children.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

Section 8: Exposure Controls/Personal Protection

US Exposure Limits:

Revision Date: 2/26/2015 Page 3 of 10

Chemical Ingredients:	CAS Number:	OSHA PEL	NIOSH REL	ACGIH TLV
Isopropyl Alcohol	67-63-0	400 ppm	400 ppm (TWA) 500 ppm (STEL) 2000 ppm (IDLH)	200 ppm (TWA) 400 ppm (STEL)
L-Menthol	2216-51-5	Not Established	Not Established	Not Established
Glycerine (as mist)	56-81-5	15 mg/m ³	Not Established	10 mg/m ³

Other Exposure Limits:

Isopropyl Alcohol:

Indonesia:

Belgium:

China: 700 mg/m³ STEL; 350 mg/m³ TWA Hong Kong: 500 ppm STEL; 1230 mg/m³ STEL;

400 ppm TWA; 983 mg/m³ TWA 500 ppm STEL; 1230 mg/m³ STEL;

400 ppm TWA; 983 mg/m³ TWA

Japan: 200 ppm Administrative Control Level (ACL)

Korea: 400 ppm Ceiling; 980 mg/m³ Ceiling 400 ppm STEL; 980 mg/m³ STEL; 200 ppm TWA; 480 mg/m³ TWA

Malaysia: 400 ppm TWA; 980 mg/m³ TWA
Philippines: 400 ppm TWA; 980 mg/m³ TWA
Singapore: 500 ppm STEL; 1230 mg/m³ STEL;

400 ppm TWA; 983 mg/m³ TWA

Taiwan: 500 ppm STEL; 1228.75 mg/m³ STEL;

400 ppm TWA; 983 mg/m³ TWA

Russia: 50 mg/m³ STEL (vapor); 10 mg/m³ TWA (vapor) Austria: 800 ppm STEL; 2000 mg/m³ STEL (4 x 15 min)

800 ppm STEL; 2000 mg/m³ STEL (4 x 30 min)

200 ppm MAK; 500 mg/m³ MAK; 400 ppm STEL; 1000 mg/m³ STEL;

200 ppm TWA; 500 mg/m³ TWA

Bulgaria: 1225.0 mg/m³ STEL; 980.0 mg/m³ TWA Czech Republic: 500 mg/m³ TWA; 1000 mg/m³ Ceiling Denmark: 200 ppm TWA; 490 mg/m³ TWA

Estonia: 250 ppm TWA; 450 mg/m³ STEL; 150 ppm TWA; 350 mg/m³ TWA

Finland: 250 ppm STEL; 620 mg/m³ STEL;

200 ppm TWA; 500 mg/m³ TWA France: 400 ppm TWA; 980 mg/m³ STEL Germany: 400 ppm Peak; 1000 mg/m³ Peak;

200 ppm MAK; 500 mg/m³ MAK

Greece: 500 ppm STEL; 1225 mg/m³ STEL;

400 ppm TWA; 980 mg/m³ TWA

 Hungary:
 2000 mg/m³ STEL; 500 mg/m³ TWA

 Ireland:
 400 ppm STEL; 200 ppm TWA

 Italy:
 400 ppm STEL; 200 ppm TWA

 Latvia:
 600 mg/m³ STEL; 350 mg/m³ TWA

 Lithuania:
 250 ppm STEL; 600 mg/m³ STEL;

150 ppm TWA; 350 mg/m³ TWA

Netherlands: 10000 mg/m³ Life Threatening Value (LBW); 200 mg/m³

Prescribed Target Value (VRW); 2000 mg/m³ Warning Limit

Value (AGW)

Poland: 1200 mg/m³ STEL; 900 mg/m³ TWA

> 400 ppm STEL; 200 ppm TWA Portugal: 203 ppm STEL; 500 mg/m³ STEL; Romania:

> > 81 ppm TWA; 200 mg/m³ TWA

1000 mg/m³ Ceiling; 200 ppm TWA; 500 mg/m³ TWA Slovakia:

800 ppm STEL; 2000 mg/m³ STEL; Slovenia: 200 ppm TWA; 500 mg/m³ TWA 500 ppm STEL; 1250 mg/m³ STEL; Spain:

400 ppm TWA; 998 mg/m³ TWA

Sweden: 250 ppm STEL; 600 mg/m³ STEL;

150 ppm TLV; 350 mg/m³ TLV

United Kingdom: 500 ppm STEL; 1250 mg/m³ STEL;

400 ppm TWA; 999 mg/m³ TWA

L-Menthol:

1 mg/m³ (aerosol and vapor) Russia:

Glycerine:

10 mg/m³ TWA (mist, inhalable particulates) Indonesia:

10 mg/m³ TWA (mist) 10 mg/m³ TWA (mist) Korea: Malaysia: Singapore: 10 mg/m³ PEL (mist) 10 mg/m³ TWA (mist) Belgium:

Czech Republic: 10 mg/m³ TWA; 15 mg/m³ Ceiling

10 mg/m³ TWA Estonia: Finland:

20 mg/m³ TWA 10 mg/m³ TWA (aerosol) France:

100 mg/m³ Peak (inhalable fraction); 50 mg/m³ MAK (inhalable Germany:

fraction)

10 mg/m³ TWA Greece: 10 mg/m³ TWA 10 mg/m³ TWA 10 mg/m³ TWA (aerosol) Ireland: Italy:

Poland: 10 mg/m³ TWA (mist) Portugal:

10 mg/m³ TWA Spain:

United Kingdom: 30 mg/m³ STEL (calculated, mist); 10 mg/m³ TWA (mist)

Engineering Controls: Use only in a well-ventilated area.

Personal Protective Equipment:

Eye Protection: None required under normal conditions of use.

Hand Protection: Not Applicable

Skin and Body Protection: Not Applicable

Respiratory Protection: None required under normal conditions of use.

Hygiene Measures: Wash hands thoroughly after handling. Use only in a well-ventilated area.

Section 9: Physical and Chemical Properties

Physical State: Gel
Color: Colorless

Odor: Menthol Scented **Odor Threshold:** Not Available pH: 6.0 - 7.0Melting/Freezing Point: Not Available Initial Boiling Point: Not Available Flash Point: ≥73.4°F (≥23°C) **Evaporation Rate:** Not Available Flammability (solid, gas): Not Applicable Lower Explosive Limit: Not Available **Upper Explosive Limit:** Not Available

Lower Flammability Limit: 20% Upper Flammability Limit: 35%

Vapor Pressure:Not AvailableVapor Density:Not AvailableRelative Density:0.95 ± 0.05Water Solubility:CompletePartition Coefficient:Not AvailableAutoignition Temperature:Not AvailableDecomposition Temperature:Not AvailableViscosity:Not Available

Section 10: Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Sources of ignition, heat, sunlight, pressure.

Incompatible Materials: Strong acids and oxidizers.

Hazardous Decomposition Products: Alcoholic vapors.

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information

Inhalation: No known effects.

Ingestion: May be harmful if swallowed.

Skin Contact: Relieves pain when used in accordance with instructions.

Eye Contact: May cause eye irritation.

Chronic Exposure: No known effects.

Aggravation of Pre-existing Conditions: No information found.

Numerical Measures of Toxicity: None available.

Carcinogenicity: Not known to be as defined by OSHA, IARC or NTP.

Section 12: Ecological Information

This product is safe for the environment at the concentrations predicted under normal use conditions.

Section 13: Disposal Considerations

Dispose of contents/container in accordance with all applicable local, state and national regulations.

Section 14: Transport Information

US DOT:

Proper shipping name: Flammable liquid nos (contains isopropyl alcohol)

Hazard class: 3 Flammable liquid

UN Number: UN 1993

Packing Group:

Labels: Flammable Liquid Class 3

If a Limited Quantity (49CFR 173.150) then ship as follows:

Proper shipping name: Not required. Hazard class: Not required. UN Number: Not required.

Labels: Use ground limited quantity label.

DOT Hazardous Substance RQ: None/no reportable quantities DOT Marine Pollutants: None/no reportable quantities

IATA:

Proper shipping name: Flammable liquid nos (contains isopropyl alcohol)

Hazard class: 3 Flammable liquid

UN Number: UN 1993

Packing Group: III

Labels: Flammable Liquid, Air limited quantity Y label.

If a Limited Quantity (49CFR 173.150) then ship as follows:

Proper shipping name: ID8000 Consumer Commodity

Hazard class: 9 Miscellaneous
UN Number: Not required
Packing Group: Not Required

Labels: Class 9 Miscellaneous, Air limited quantity Y label.

IMDG (All domestic and international shipments by Ocean)

Proper shipping name: Flammable liquid nos (contains isopropyl alcohol)

Hazard Class: 3 (Flammable)
UN Number: UN1993
Packing Group: III

Labels: Flammable Liquid

If a Limited Quantity (49CFR 173.150) then ship as follows:

Proper shipping name: Flammable liquid nos(contains isopropyl alcohol), LTD. QTY.

Hazard Class: 3 (Flammable)
UN Number: UN1993

Packing Group: III

Labels: Limited Quantity

Section 15: Regulatory Information

US Regulatory Information:

OSHA Hazards: Flammable, Irritant

SARA 302: None/no reportable quantities.

SARA 311/312 Hazard Categories: Fire Hazard, Acute Health Hazard

SARA 313: Isopropyl Alcohol (CAS #67-63-0) is subject to SARA 313 reporting

requirements.

TSCA: All substances in this product are listed on the TSCA inventory if required.

Canadian Regulatory Information:

DSL List: All components of this product comply with registration requirements.

European Economic Community Information for Constituents: The following information is available for the components of this product:

Isopropyl Alcohol: EU EINECS/ELINCS Number: 200-661-7

Glycerin: EU EINECS/ELINCS Number: 200-289-5

Propylene Glycol: EU EINECS/ELINCS Number: 200-338-0

L-Menthol: EU EINECS/ELINCS Number: 218-690-9

EU Labeling and Classification According to Directive 1999/45/EC: This product meets the definition of the following hazard class as defined by the European Economic Community Guidelines.

EU Classification: [R10] Flammable, [Xi] Irritant

EU Risk Phrases: R10: Flammable; R36: Irritating to eyes; R67: Vapors may cause drowsiness or dizziness.

EU Safety Phrases: S2: Keep out of reach of children; S7: Keep container tightly closed; S16: Keep away from sources of ignition – No smoking; S25: Avoid contact with eyes; S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Revision Date: 2/26/2015 Page 8 of 10

EU Symbols:



Japanese Information:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I Specified Chemical Substances or Class II Specified Chemical Substances by the Japanese MITI. Contains less than 1% methyl 4-hydroxybenzoate, which is a Class I Designated Chemical Substance.

Japanese ENCS Inventory: The components of this product are on the ENCS Inventory if required.

Poisonous and Deleterious Substances Control Law: No component of this product is a listed poisonous, deleterious, or specified poisonous substance under the Poisonous and Deleterious Substances Control Law.

Other International Chemical Inventories:

China Inventory of Existing Chemical Substances (IECSC): The components of this product are on the IECSC if required.

Korean Existing Chemicals List (KECL): The components of this product are on the KECL if required.

Philippines Inventory of Chemicals and Chemical Substances (PICCS): The components of this product are on the PICCS if required.

Section 16: Other Information

The information contained in this MSDS is presented in good faith and believed to be accurate based on the information provided. The MSDS does not purport to be all inclusive, and shall be used only as a guide. While Performance Health, Inc. believes that the data contained herein comply with 29 CFR 1910.1200, they are not to be taken as a warranty or representation for which Performance Health, Inc. assumes legal responsibility. Performance Health, Inc. shall not be held liable or accountable for any loss or damage associated with the use of this material and information. The recommended industrial hygiene and safe use, handling, storage, and disposal procedures are believed to be generally applicable. However, since the use, handling, storage, and disposal are beyond Performance Health, Inc. control, it is the responsibility of the user both to determine safe conditions for use of this product and to assume liability of loss, damage, or expense arising out of the material's improper use.

HMIS Classification:

Health Hazard: 1 Flammability: 2 Physical Hazards: 0

Legend:

ACGIH: American Conference of Governmental & Industrial Hygienists

CAS: Chemical Abstract Service **CFR:** Code of Federal Regulations

DOT: Department of Transportation

DSL/NDSL: Domestic Substances List/Non-Domestic Substances List

EC Number: EINECS Number or ELINCS Number

EINECS: European Inventory of Existing Commercial Chemical Substance

ELINCS: European List of Notified Substance **ENCS:** Existing and New Chemical Substances

EU: European Union

GHS: Globally Harmonized System of Chemical Classification and Labelling

HMIS: Hazardous Materials Identification System **IARC:** International Agency for the Research of Cancer

IATA: International Air Traffic Association ICAO: International Civil Aviation Organization IDLH: Immediately Dangerous to Life or Health IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organizations

MAK: Maximala Arbeitapletzkenzentration (F.

MAK: Maximale Arbeitsplatzkonzentration (Exposure Limit) **NIOSH:** National Institute of Occupational Safety and Health

NTP: National Toxicology Program

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety & Health Administration

PEL: Permissible Exposure Limits

RCRA: Resource Conservation & Recovery Act

REL: Recommended Exposure Limits

RQ: Reportable Quantity **RTK:** Right-To-Know

SARA: Superfund Amendments & Reauthorization Act

STEL: Short Term Exposure Limit

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

TCLP: Toxicity Characteristic Leaching Procedure

US: United States

VOC: Volatile Organic Compounds