



Wall Power® Foaming Wall Washer

Revision: 2021-12-08

Version: 03.0

1. IDENTIFICATION

Product name: Wall Power®
Foaming Wall Washer

SDS #: MS0800386

Recommended use:

- General purpose cleaner
- Industrial/Institutional
- This product is intended to be used neat.

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier:

| | |
|--|---|
| US Headquarters Diversey, Inc. 1300 Altura Rd., Suite 125 Fort Mill, SC 29708 Phone: 1-888-352-2249 SDS Internet Address: https://sds.diversey.com | Canadian Headquarters Diversey Canada, Inc. 6150 Kennedy Road Unit 3 Mississauga, Ontario L5T 2J4 Phone: 1-800-668-7171 |
|--|---|

Emergency telephone number: 1-800-851-7145; 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

| | |
|--|---|
| Serious eye damage/eye irritation | Category 2A |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Flammability | Extremely flammable aerosol, Category 1 |
| Gases under pressure | Liquified gas |

**Signal word:****Danger.**

Hazard Statements

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. CAUSES SERIOUS EYE IRRITATION.

Precautionary Statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not incinerate. Do not breathe spray. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. May cause irritation to mouth, throat and stomach. Wear chemical-splash goggles and chemical-resistant gloves. IF SWALLOWED: Call a Poison Center or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice or attention. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION: DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Mix only with water. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat.

Health hazards not otherwise classified (HHNOC) - Not applicable
Physical hazards not otherwise classified (PHNOC) - Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

| Ingredient(s) | CAS # | Weight % |
|--------------------------|----------|------------|
| Butane | 106-97-8 | 1 - 5% |
| Ethyl alcohol | 64-17-5 | 1 - 5% |
| Propane | 74-98-6 | 0.5 - 1.5% |
| Tetrasodium salt of EDTA | 64-02-8 | 0.5 - 1.5% |

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin: Rinse with plenty of water.

Inhalation: No specific first aid measures are required.

Ingestion: IF SWALLOWED: Call a Poison Center (1-800-851-7145) or doctor/physician if you feel unwell.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

5. FIRE-FIGHTING MEASURES

Specific methods: Use water spray to keep fire-exposed containers cool Aerosol Product - Containers may rocket or explode in heat of fire

Suitable extinguishing media: Dry chemical, water spray, foam, carbon dioxide.

Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions and clean-up methods: Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat. Do not mix with other products or chemicals except as directed on the label. Mix only with water. EXTREMELY FLAMMABLE AEROSOL. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. PRESSURIZED CONTAINER: Do not pierce or burn, even after use. Do not incinerate. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not taste or swallow. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Remove and wash contaminated clothing and footwear before re-use. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: NFPA 30B Level 1 Aerosol. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting.

Aerosol Level (if applicable): Level 1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

| Ingredient(s) | CAS # | ACGIH | OSHA |
|---------------|----------|-----------------|--|
| Butane | 106-97-8 | 1000 ppm (STEL) | |
| Ethyl alcohol | 64-17-5 | 1000 ppm (STEL) | 1000 ppm (TWA) 1900 mg/m ³ (TWA) |
| Propane | 74-98-6 | | 1000 ppm (TWA) 1800 mg/m ³ (TWA) |

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

It is the responsibility of the employer to determine the potential risk of exposure to hazardous chemicals for employees in the workplace in order to determine the necessity, selection, and use of personal protective equipment.

| | |
|----------------------------------|--|
| Eye protection: | Chemical-splash goggles. |
| Hand protection: | Chemical-resistant gloves. |
| Skin and body protection: | No personal protective equipment required under normal use conditions. |
| Respiratory protection: | In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. |
| Hygiene measures: | Handle in accordance with good industrial hygiene and safety practice. |

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid

Evaporation Rate: No information available

Odor threshold: No information available.

Melting point/freezing point (°C): Not determined

Autoignition temperature: No information available

Solubility in other solvents: No information available

Density: 1.011 Kg/L

Bulk density: No information available

Flash point (°F): -156°F ≈ -104.4 °C

Viscosity: No information available

VOC: 7.9 % *

Flammability (Solid or Gas): Not applicable

Sustained combustion: Not applicable

Explosion limits: - upper: Not determined **- lower:** Not determined

Color: Cloudy , Yellow

Odor: Floral

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: No information available

Relative Density (relative to water): 1.01

Vapor density: No information available

Vapor pressure: No information available.

Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0.00 % by wt.

pH: 12

Corrosion to metals: Not corrosive to metals

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:

Not Applicable

Stability:

The product is stable

Possibility of hazardous reactions:

May vigorously react with acids resulting in spattering and excessive heat.

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid:

Acids. Strong acids. Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid:

Extremes of temperature and direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: May be mildly irritating to skin. Symptoms may include redness and/or transient discomfort.

Eye contact: Causes serious eye irritation. Symptoms may include pain, redness, and watering.

Ingestion: Symptoms may include stomach pain and nausea. May be irritating to mouth, throat and stomach.
Inhalation: Symptoms may include coughing and difficulty breathing. May be irritating to nose, throat, and respiratory tract.
Sensitization: No known effects.
Target Organs (SE): None known
Target Organs (RE): No information available

Numerical measures of toxicity

ATE - Oral (mg/kg): The estimated acute oral LD₅₀ for the undiluted product is estimated to be >5000 (mg/kg BW).
ATE - Dermal (mg/kg): >2000
ATE - Inhalatory, gases (mg/l): >20,000
ATE - Inhalatory, mists (mg/l): >20
ATE - Inhalatory, vapors (mg/l): > 20

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.
Persistence and Degradability: No information available.
Bioaccumulation: No information available.
Mobility: No information available.
Other adverse effects No other adverse effects known.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products (undiluted product): This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.
RCRA Hazard Class (undiluted product): D001 Ignitable Waste
Contaminated Packaging: Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: The information provided below is the full transportation classification for this product. This description does not account for the package size(s) of this product, that may fall under a quantity exception, according to the applicable transportation regulations. When shipping dangerous goods, please consult with your internal, certified hazardous materials specialist to determine if any exceptions can be applied to your shipment.
DOT (Ground) Bill of Lading Description: UN1950, AEROSOLS, FLAMMABLE, 2.1
IMDG (Ocean) Bill of Lading Description: UN1950, AEROSOLS, FLAMMABLE, 2.1

15. REGULATORY INFORMATION

International Inventories at CAS# Level
TSCA All components are listed or otherwise exempt
DSL All components are listed or otherwise exempt

US RIGHT TO KNOW (RTK)

| Ingredient(s) | CAS # | MARTK: | NJRTK: | PARTK: | RIRTK: |
|---------------|-----------|--------|--------|--------|--------|
| Water | 7732-18-5 | - | - | - | - |

| | | | | | |
|-----------------------------|-------------|---|---|---|---|
| Butane | 106-97-8 | X | X | X | - |
| Ethyl alcohol | 64-17-5 | X | X | X | - |
| Propane | 74-98-6 | X | X | X | - |
| Trade Secret | Proprietary | - | - | - | - |
| Tetrasodium salt of EDTA | 64-02-8 | - | - | - | - |
| Sodium hydroxide | 1310-73-2 | X | X | X | X |
| Tert-butyl alcohol | 75-65-0 | X | X | X | - |
| trisodium nitrilotriacetate | 5064-31-3 | X | - | - | - |

CERCLA/ SARA

Canadian Regulations

| Ingredient(s) | CAS # | NPRI |
|---------------|---------|------|
| Ethyl alcohol | 64-17-5 | X |
| Propane | 74-98-6 | X |

16. OTHER INFORMATION

NFPA (National Fire Protection Association)
 Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 2
Flammability 4
Instability 0
Special Hazards -

Revision: 2021-12-08
Version: 03.0

Reason for revision: Not applicable
Prepared by: North American Regulatory Affairs
Additional advice: • Contains an added fragrance, see "Odor" heading in section 9 for specific description

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.