



BREAK-UP® Professional Oven & Grill Cleaner

Version Number: 3

Preparation date: 2018-08-24

1. IDENTIFICATION

Product name: BREAK-UP® Professional Oven & Grill Cleaner
Product Code: CBD991206
SDS #: MS0801099
Recommended use:

- Industrial/Institutional
- Oven and Grill Cleaner
- This product is intended to be used neat.

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 2415 Cascade Pointe Blvd. Charlotte, NC 28208 Phone: 1-888-352-2249 SDS Internet Address: https://sds.diversey.com	Canadian Headquarters Diversey Canada, Inc. 3755 Laird Road Units 8-11 Mississauga, Ontario L5L 0B3 Phone: 1-800-668-7171
---	---

Emergency telephone number: 1-800-851-7145; 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation	Category 1B
Serious eye damage/eye irritation	Category 1
Flammability	Extremely flammable aerosol, Category 1
Metal Corrosion:	Category 1



Signal Word:

Danger.

Hazard and Precautionary Statements

EXTREMELY FLAMMABLE AEROSOL. CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS. Causes burns/ serious damage to mouth, throat and stomach. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Keep only in original container. Do not pierce or burn, even after use. Do not incinerate. Do not breathe the vapor or spray. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, long chemical-resistant gloves, protective clothing and protective footwear when spraying and wiping. Do not spray towards face. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Absorb spillage to prevent material damage. Store in corrosive-resistant container with a resistant inner liner. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION: DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Mix only with water. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat.

Health hazards not otherwise classified (HHNOC) - Not applicable
Physical hazards not otherwise classified (PHNOC) - Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS #	Weight %
Diethylene glycol butyl ether	112-34-5	10 - 20%
Sodium hydroxide	1310-73-2	3 - < 5%
Butane	106-97-8	1 - < 3%
Isobutane	75-28-5	1 - < 3%
Monoethanolamine	141-43-5	1 - < 3%

*Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: Burning. Coughing and/ or wheezing.

Immediate medical attention and special treatment needed Not applicable.

5. FIRE-FIGHTING MEASURES

Specific methods:

No special methods required

Suitable extinguishing media:

Dry chemical, water spray, foam, carbon dioxide.

Specific hazards:

Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol. Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate cans. Use personal protective equipment. Do not get in eyes, on skin, or on clothing.

Environmental precautions and clean-up methods:

Eliminate all ignition sources. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. ALWAYS WEAR LONG CHEMICAL-RESISTANT GLOVES, CHEMICAL-SPLASH GOGGLES AND PROTECTIVE FOOTWEAR WHEN SPRAYING AND WIPING. Do not spray toward face. Wash hands and arms after use. Do not spray on or let spray contact pilot light, electrical connections, switches, light bulbs, heating elements, receptacles, or thermostats. Spray may cause electric short. Do not let product contact floor coverings, linoleum, aluminum, copper, chrome, painted surfaces or plastics. Do not use on continuous or self-cleaning ovens. Do not taste or swallow. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Can react to release hazardous gases. EXTREMELY FLAMMABLE AEROSOL. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. PRESSURIZED CONTAINER: Do not pierce or burn, even after use. Do not incinerate. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Mix only with water. Do not mix with any other product or chemical. May vigorously react with acids resulting in spattering and excessive heat. Absorb spillage to prevent material damage. FOR COMMERCIAL AND

INDUSTRIAL USE ONLY.

Storage: NFPA 30B Level 1 Aerosol. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C (122 °F) which may cause bursting. Store in corrosive-resistant container with a resistant inner liner.

Aerosol Level (if applicable) : Level 1

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS #	ACGIH	OSHA
Diethylene glycol butyl ether	112-34-5	10 ppm (TWA)	-
Sodium hydroxide	1310-73-2	2 mg/m ³ (Ceiling)	2 mg/m ³ (TWA)
Butane	106-97-8	1000 ppm (STEL)	-
Isobutane	75-28-5	1000 ppm (STEL)	-
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

Eye protection:	Chemical-splash goggles.
Hand protection:	Chemical-resistant gloves.
Skin and body protection:	If major exposure is possible, wear suitable protective clothing and footwear.
Respiratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol

Evaporation Rate: No information available

Odor threshold: No information available.

Melting point/range: Not determined

Autoignition temperature: No information available

Solubility in other solvents: No information available

Density: 8.75 lbs/gal 1.049 Kg/L

Bulk density: No information available

Flash point (°F): 19.4 °F -7 °C

Viscosity: No information available

VOC: 8.1 % *

Flammability (Solid or Gas): Not applicable

Sustained combustion: Not applicable

Explosion limits: - upper: Not determined - **lower:** Not determined

Color: Opaque Tan

Odor: Citrus Slightly perfumed

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Dispersible

Relative Density (relative to water): 1.049

Vapor density: No information available

Vapor pressure: No information available.

Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0.00 % by wt.

pH: 13

Corrosion to metals: Corrosive

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:	Not Applicable
Stability:	The product is stable
Possibility of hazardous reactions:	May vigorously react with acids resulting in spattering and excessive heat.
Hazardous decomposition products:	None reasonably foreseeable.
Materials to avoid:	Strong bases. Ammonia. Do not mix with chlorinated products (such as bleach). Do not mix with any other product or chemical unless specified in the use directions. Strong acids.
Conditions to avoid:	Extremes of temperature and direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed).

Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Target Organs (SE): None known

Target Organs (RE): None known

Numerical measures of toxicity

ATE - Oral (mg/kg): >5000

ATE - Dermal (mg/kg): >5000

ATE - Inhalatory, mists (mg/l): >20

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products (undiluted product): This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

RCRA Hazard Class (undiluted product): D001 Ignitable Waste D002 Corrosive Waste

Contaminated Packaging: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT (Ground) Bill of Lading Description: LTD. QTY.

IMDG (Ocean) Bill of Lading Description: UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).



WARNING: This product can expose you to chemicals including diethanolamine, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Diethylene glycol butyl ether	112-34-5	-	X	-	-
Sodium hydroxide	1310-73-2	X	X	X	X
Butane	106-97-8	X	X	X	-
Isobutane	75-28-5	X	X	X	-

Monoethanolamine	141-43-5	X	X	X	-
------------------	----------	---	---	---	---

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Diethylene glycol butyl ether	112-34-5	10 - 20%			X
Sodium hydroxide	1310-73-2	3 - < 5%	1000		

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	X		

Canadian Regulations

Ingredient(s)	CAS #	NPRI
Diethylene glycol butyl ether	112-34-5	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3

Flammability 4

Instability 0

Version Number: 3

Preparation date: 2018-08-24

Reason for revision:

Not applicable

Prepared by:

NAPRAC

Additional advice:

• Contains an added fragrance, see "Odor" heading in section 9 for specific description

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.