

Safety Data Sheet

41101 Mötsenböcker's LIFT OFF® Spray Paint & Graffiti Remover

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Mötsenböcker's LIFT OFF® Spray Paint & Graffiti Remover
Product Code: 41101
Product Use: Graffiti & Paint Remover
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A

Signal Word Danger

Hazard Statements Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.

Precautionary Statements

Prevention Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
P264 - Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Response P302+P352 - If on skin: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
P321 - Specific treatment (see on this SDS).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use proper media to extinguish.

Storage Keep container tightly closed.
Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>Percent</u>
2-propanone	67-64-1	1-20
Glycol ether	111-76-2	1-20
Glycol ether	112-34-5	1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 2* Flammability: 3 Physical: 0 Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
 Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
 Ingestion: Do not induce vomiting. Contact a physician, medical facility, or poison control center immediately.
 Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

This material (or a component) may cause acidosis. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. "Empty" containers retain product residue and can be dangerous.
 Fire Fighting Instructions: Use alcohol foam, water fog, dry chemical, or CO2. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Avoid run-off into storm sewers and ditches which may lead to natural waterways. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Use with adequate ventilation. Normal precautions common to safe manufacturing practice should be followed in handling and storage. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
 Storage: Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Normal precautions common to safe manufacturing practice should be followed in handling and storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
 Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
 Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
 Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
2-propanone	67-64-1	500 ppm TWA	Not established	Not established
Glycol ether	111-76-2	20 ppm [skin]	Not established	Not established
Glycol ether	112-34-5	20ppm	50ppm	35ppm TWA (Mfg. recommend)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk trigger bottle	Lower Flammability Limit (%):	0.9
Appearance:	Clear to hazy.	Upper Flammability Limit (%):	13
Odor:	Citrus	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Mild	Vapor Density [air = 1]:	> 1
pH:	Not applicable	Relative Density (H2O=1):	0.98
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Complete; 100%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	51.0	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	1-20		

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Oxidizers. Excessive heat. Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Strong alkalis.
Decomposition Products:	Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.
IARC Carcinogen Designation:	No data available

Ingredient	CAS #	Toxicological Data
2-propanone	67-64-1	DERMAL LD50 GUINEA PIG 9400 UL/KG ORAL LD50 Mouse 3 GM/KG
Glycol ether	111-76-2	INHALATION LC50 Rat 50100 MG/M3 DERMAL LD50 Rabbit 220 mg/kg ORAL LD50 GUINEA PIG 1200 mg/kg ORAL LD50 Rat 250 mg/kg
Glycol ether	112-34-5	INHALATION LC50 Rat 2900 MG/M3 INHALATION LC50 Mouse 700 ppm INHALATION LC50 Mouse 3380 MG/M3 ORAL LD50 GUINEA PIG 2000 mg/kg ORAL LD50 Mouse 2400 mg/kg ORAL LD50 Mouse 4500 mg/kg ORAL LD50 Mouse 6050 mg/kg

12. ECOLOGICAL INFORMATION

Ecological Toxicity:	No data available
Mobility:	No data available
Degradability:	No data available.

Ingredient	CAS #	Toxicological Data
2-propanone	67-64-1	Aquatic LC50 (48h) Rainbow Trout = 6100 mg/L 48HR EC50 Daphnia = 7630 mg/L No data available
Glycol ether	111-76-2	Aquatic LC50 (96h) MINNOW = 72860 mg/L Aquatic LC50 (48h) Daphnia > 100 mg/L Aquatic LC50 (96h) Algae 6500 - 13000 mg/L
Glycol ether	112-34-5	Aquatic LC50 (96h) Bl gill = 1300 mg/L Aquatic LC50 (24h) Daphnia = 2850 mg/L No data available

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1993	Flammable Liquids, n.o.s.(Contains Acetone)	3	II
IATA	UN1993	Flammable Liquids, n.o.s.(Contains Acetone)	3	II
IMDG	UN1993	Flammable Liquids, n.o.s.(Contains Acetone)	3	II

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 05/07/18

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.