



## MATERIAL SAFETY DATA SHEET

**NAME: NANFU(EXCELL) ALKALINE BATTERIES  
LR20(D);LR14(C);LR6(AA);LR03(AAA);6LR61(9V)**

**CAS No.: Not applicable**

### 1. IDENTIFICATION

Manganese Dioxide (CAS No.:1313-13-9)	36%-43%
Zinc (CAS No.:7440-66-6)	13%-18%
Potassium Hydroxide (40%) (CAS No.:1310-58-3)	4%-9%
Graphite, natural (CAS No.:7782-42-5)	1%-4%
Zinc Oxide (CAS No.:1314-13-2)	<1

### 2. PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance And Odor: N/R	Boiling Point: N/R	Melting Point: N/R
Vapor Pressure (MM Hg/70 F): N/R	Vapor Density (Air=1): N/R	Specific Gravity: N/R
Decomposition Temperature: UNKNOWN	Evaporation Rate And Ref: N/R	Solubility In Water: N/R
Percent Volatiles By Volume: N/R	Viscosity: N/R	pH: N/R
Corrosion Rate (IPY): UNKNOWN	Autoignition Temperature: N/R	

### 3. REACTIVITY

Stability: YES	Polymerization: Will not occur
Condition to avoid: Avoid electrical shorting	Materials to avoid: Not applicable
Hazardous Decomposition Products: Thermal degradation may produce hazardous fumes of zinc and manganese; Hydrogen gas; caustic vapors of potassium hydroxide and other toxic by-products.	

### 4. HEALTH HAZARD DATA

LD50-LC50 Mixture: LD 50 oral rat is unknown
Route of entry - Inhalation: NO
Route of entry - Skin: YES
Route of entry - Ingestion: NO
Health Haz Acute And Chronic: No health hazard unless battery ruptures. In that event, It may cause burns and irritation.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO

## 5. EXPOSURE CONTROL METHODS

Engineering Controls	General ventilation under normal use conditions.
Eye Protection	None under normal use conditions. Wear safety glasses when handling leaking batteries.
Skin Protection	None under normal use conditions. Use neoprene, rubber or latex gloves when handling leaking batteries.
Respiratory Protection	None under normal use conditions.
Other	Keep batteries away from small children.

## 6. HANDLING AND STORAGE

Store at room temperature. Avoid mechanical or electrical abuse. Do not short or install incorrectly. Batteries may explode, pyrolyze or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Do not mix battery systems, such as alkaline and zinc carbon, in the same equipment. Replace all batteries in equipment at the same time. Do not carry batteries loose in pocket or bag. Do not remove battery label.
---

## 7. WASTE DISPOSAL METHODS

Individual consumers may dispose of spent (used) batteries with household trash. Nanfu does not recommend that spent batteries be accumulated (quantities of five gallons or more should be disposed of in a secure landfill), in accordance with appropriate federal, state and local regulations. Do not incinerate, since batteries may explode at excessive temperatures.
---

## 8. EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area	Notify safety personnel of large spills. Caustic potassium hydroxide may be released from leaking or ruptured batteries. Avoid eye or skin contact and inhalation of vapors. Increase ventilation. Clean-up personnel should wear appropriate protective gear.
Fire and Explosion Hazard	Batteries may burst and release hazardous decomposition products when exposed to a fire situation. See Sec. 3.
Extinguishing Media	As appropriate for surrounding area.
Firefighting Procedures	Use self-contained breathing apparatus and full protective gear.

## 9. FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes	Not anticipated. If battery is leaking and material contacts eyes, flush with copious amounts of clear, tepid water for 30 minutes. Contact physician at once.
Skin	Not anticipated. If battery is leaking, irrigate exposed skin with copious amounts of clear, tepid water for at least 15 minutes. If irritation, injury or pain persists, consult a physician.
Inhalation	Not anticipated. If battery is leaking, contents may be irritating to respiratory passages. Remove to fresh air. Contact physician if irritation persists.
Ingestion	Not anticipated. Rinse the mouth and surrounding area with clear, tepid water for at least 15 minutes. Consult a physician immediately for treatment and to rule out involvement of the esophagus and other tissues.
Notes to Physician	<ol style="list-style-type: none"><li>1) The primary acutely toxic ingredient is concentrated (40%) potassium hydroxide.</li><li>2) Anticipated potential leakage of potassium hydroxide is 1-3 ml, depending on battery size.</li><li>3) This MSDS does not include or address the small button cell batteries, which can be ingested.</li></ol>

# MATERIAL SAFETY DATA SHEET

In Accordance with Directive 2001/58/CE

Date: 01/01/2011

## 1. Chemical Product

MSDS Name: Alkaline Battery

Manufacturer: **SICHUAN CHANGHONG NEWENERGY TECHNOLOGY CO., LTD.**

Address: No.35, East Mianxing Road, High-Tech Park, 621000, Mianyang, Sichuan, China.

Tel: +86-816-2418674

Fax: +86-816-2410586

## 2. Composition /Information on Ingredients:

Chemical Nature: Chemical power source

CAS-No/EINECS NO.: Not applicable.

INCI CTFA-Description: Alkaline Zinc-Manganese Dry Battery

Tariff No.: "W" 85.06

IMPORTANT NOTE: The battery shall not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

Chemical Name	Molecular Formula	CAS No.	Weight (%)
Zinc	Zn	7440-66-6	17~25
Manganese Dioxide	MnO <sub>2</sub>	1313-13-9	35~43
Graphite	C	7782-42-5	3~4
Potassium hydroxide (liquid)	KOH	1310-58-3	9~12.5
Copper	Cu	7440-50-8	1
Iron	Fe	7439-89-6	15~18
Water	H <sub>2</sub> O	7732-18-5	10~12
Nylon	---	24937-16-4	2~3

\* PNOR: Particulates not otherwise regulated

\*\* PNOC: Particulates not otherwise classified

## 3. Hazards identifications

General: Alkaline battery --- The Common known rules for handing of chemical power source should be obeyed. Do not heat, recharge, disassemble the product or dispose of in fire.

Physical-Chemical Hazards: The chemical materials concluded in the Product is sealed up, thus being stable, safe and eco-friendly under common conditions, may not cause physical-chemical hazards.

Hazards to Human being: Disassemble the product without a professional basis, may cause leakage of the electrolyte and irritation to skin; or cause Hg/ Cd/ Pb (micro trace) poisoning.

Hazards to environment: Dispose the product without separate collection, may lead to pollution caused by Hg/ Cd/ Pb (micro trace), or the electrolyte of alkali solution.

# MATERIAL SAFETY DATA SHEET

In Accordance with Directive 2001/58/CE

Date: 01/01/2011

## 4. First-aid measures

Inhalation: Not applicable.

Skin Contact: Wash with clear water immediately once leakage happens and the inner liquid splashes onto skin.

Eye contact: Rinse eyes immediately with running water for at least ten minutes. Consult an ophthalmologist.

Ingestion: Rinse mouth with water; Give plenty of water to drink. Obtain medical advice.

## 5. Fire-fighting measures

Suitable extinguishing media: Carbon dioxide (CO<sub>2</sub>), foam, dry chemical powder.

Extinguishing media not to be used: Never use a direct water jet, may pollute the water system.

Exposure hazards from combustion products: In case of fire, carbon monoxide or other toxic organic substances may be generated.

Do not inhale fumes and smoke.

Personal protective equipments: Wear full protective clothing. Use self contained breathing apparatus.

**\* Remark: It can be extinguished by car extinguisher as well.**

## 6. Accidental release measures

Personal precautions: Wear protective clothing. Keep unprotected persons away.

Environmental precautions: Avoid discharge and penetration into sewerage systems, waterways, pits, and cellars.

Methods for cleaning up: Collect spilled material with an insert standard absorbent like sand or silica. Care for well-Ventilated conditions. Recycle or dispose of the materials in an appropriate way.

## 7. Handling and storage

General: Obey the common known rules and precautions for handling with chemical power sources.

Fire/Explosion protections: Explosion may happen if short-circuit; collect spilled material with an insert standard absorbent like sand or silica.

Storage: Store product in clean, cool and ventilated place with a temperature between 10°C and 30°C (no higher than 40°C in the ordinary course of events) and a relative humidity no higher than 65%; the storage time should not be too long; the batteries should be well-arranged, and do avoid short-circuit caused by the contact of the positive and negative electrodes.

## 8. Exposure controls/Personal protection

Exposition/ Technical measures: Not applicable.

Protection of hands, eyes and skin: To protect hands, eyes and skin, do not disassemble the product without professional basis.

# MATERIAL SAFETY DATA SHEET

In Accordance with Directive 2001/58/CE

Date: 01/01/2011

## 9. Physical and chemical properties

Physical state	Solid	Solubility in water	not applicable
Color	not applicable	Vapor pressure	not applicable
Odor	not applicable	Explosion limit	not applicable
pH value	not applicable	Oxidizing properties	not applicable
Specific gravity	not applicable	Flashpoint	not applicable

Refractive index	not applicable	Auto flammability	not applicable
Solubility in ethanol	not applicable	Partition coefficient	not applicable
Melting Point	not applicable	Boiling Point	not applicable
Freezing Point	not applicable		

## 10. Stability and Reactivity

The chemical materials concluded in the Product are sealed up, thus being stable, safe and eco-friendly under common conditions.

## 11. Toxicological information

The product is multi component mixture for which no toxicological data exists.

Precautions avoid disassembling the product without a professional basis.

## 12. Ecological information

In general, no ecological data is available for preparations.

Precautions avoid disposing into drainage systems and into the environment.

## 13. Disposable considerations

Precautions avoid disposing waste products into environment, sewerage, landfills or by incineration.

Obey the rules and precautions for separate collection and recycling of the waste products.

## 14. Transport Information

Road (ADR/RID) : not regulated

Air (ICAO/IATA) : not regulated

Sea (IMDG) : not regulated

\* Remark: Avoid high-temperature, high-humidity condition.

## 15. Regulatory Information

**Symbol:** for transportation, collection, or environment protection (stipulated respectively by each contract).

Contains: transportation marks;

“separate collection” symbol;

“RoHS” symbol (maybe), etc.

# MATERIAL SAFETY DATA SHEET

In Accordance with Directive 2001/58/CE

Date: 01/01/2011

## 16. Other information

The information on this Material Safety Date Sheet (MSDS) was obtained from current and reputable sources. For any other question, please contact the manufacturer for further information.

# SAFETY DATA SHEET

Air Wick Freshmatic Ultra - Pure Tropical Flowers



HEALTH • HYGIENE • HOME

## 1. Product and company identification

- Product name** : Air Wick Freshmatic Ultra - Pure Tropical Flowers
- Distributed by** : Reckitt Benckiser LLC.  
Morris Corporate Center IV  
399 Interpace Parkway (P.O. Box 225)  
Parsippany, New Jersey 07054-0225  
+1 973 404 2600
- Emergency telephone number (Medical)** : 1-800-338-6167
- Emergency telephone number (Transport)** : 1-800-424-9300 (U.S. & Canada) CHEMTREC  
Outside U.S. and Canada (North America), call Chemtrec:703-527-3887
- Website:** : <http://www.rbnainfo.com>
- Product use** : Air care, instant action (aerosol sprays)

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of USDOL Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

- SDS #** : D8282584
- Formulation #:** : #8276558\_1

### Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

## 2. Hazards identification

- Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Liquefied gas

### GHS label elements

**Hazard pictograms** :



- Signal word** : Danger
- Hazard statements** : Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

### Precautionary statements

**Code #** : FF8276558\_1

**SDS #** : D8282584

**Date of issue** : 19/09/2016.

1/12



D8282584

## 2. Hazards identification

- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
- Response** : Not applicable.
- Storage** : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
- Disposal** : Not applicable.
- Supplemental label elements** : None known.
- Hazards not otherwise classified** : None known.

## 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	> 60	64742-47-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

D8282584

## 4. First aid measures

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
irritation  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
carbonyl halides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

D8282584

## 5. Fire-fighting measures

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

D8282584

## 7. Handling and storage

**Conditions for safe storage, including any incompatibilities** : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

### Control

#### Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light	<b>ACGIH TLV (United States, 4/2014). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> , (as total hydrocarbon vapor) 8 hours.

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

D8282584

## 8. Exposure controls/personal protection

- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Aerosol.]
- Color** : Not available.
- Odor** : Characteristic.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : <34°C (<93.2°F)
- Flash point** : Closed cup: <0°C (<32°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 0.66 to 0.70
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

### Aerosol product

- Type of aerosol** : Spray
- Heat of combustion** : 40.52 kJ/g

## 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- Incompatible materials** : Do not mix with household chemicals.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

D8282584

## 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### Sensitization

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Skin contact** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
irritation  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing

**Skin contact** : No specific data.

**Ingestion** : No specific data.

D8282584

## 11. Toxicological information

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 µg/l Fresh water	Fish - Lepomis macrochirus	4 days

### Persistence and degradability

Not available.

### Bioaccumulative potential

Not available.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.






**Other adverse effects** : No known significant effects or critical hazards.

D8282584

## 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	UN1950	Aerosols	2.1	-		Limited quantity
<b>TDG Classification</b>	UN1950	AEROSOLS	2.1	-		Limited quantity
<b>Mexico Classification</b>	UN1950	AEROSOLS	2.1	-		Limited quantity
<b>IMDG Class</b>	UN1950	AEROSOLS	2.1	-		Limited quantity
<b>IATA-DGR Class</b>	UN1950	Aerosols, flammable	2.1	-		See DG List

PG\* : Packing group

## 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) PAIR**: 2-(4-tert-butylbenzyl)propionaldehyde;  $\alpha$ -hexylcinnamaldehyde; anisaldehyde; 3-p-cumenyl-2-methylpropionaldehyde; 4-(4-methyl-3-pentenyl)cyclohex-3-ene-1-carbaldehyde; phenylacetaldehyde; benzaldehyde; 2-benzylideneheptanal  
**TSCA 8(a) CDR Exempt/Partial exemption**: Not determined  
**United States inventory (TSCA 8b)**: Not determined.  
**Clean Air Act (CAA) 112 regulated flammable substances**: propane; butane; 1, 1-difluoroethane

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed



D8282584

## 15. Regulatory information

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard  
Sudden release of pressure

#### Composition/information on ingredients

No products were found.

### State regulations

**Massachusetts** : The following components are listed: PROPANE; BUTANE; DIFLUOROETHANE

**New York** : None of the components are listed.

**New Jersey** : The following components are listed: PROPANE; BUTANE; 1,1-DIFLUOROETHANE; ETHANE, 1,1-DIFLUORO-

**Pennsylvania** : The following components are listed: PROPANE; BUTANE

### Canada

**WHMIS (Canada)** : Class B-2: Flammable liquid  
Class B-5: Flammable aerosol.

### Canadian lists

**Canadian NPRI** : The following components are listed: Hydrotreated light distillate; Propane; Butane (all isomers); Volatile organic compounds

**CEPA Toxic substances** : The following components are listed: Volatile organic compounds

**Canada inventory** : Not determined.

### Label elements

**Hazard statements** :



Flammable

**Recommendations** : People suffering from perfume sensitivity should be cautious when using this product. Air Fresheners do not replace good hygiene practices.

D8282584

## 16. Other information

**Hazardous Material Information System (U.S.A.)** :

Health	2
Flammability	3
Physical hazards	0
Personal protection	B

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



NFPA (30B) aerosol Flammability Level 3

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

**Key to abbreviations** :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- UN = United Nations

**Date of issue** : 19/09/2016.

**Date of previous issue** : 21/07/2015.

**Version** : 1

**Prepared by** : Reckitt Benckiser LLC.  
Product Safety Department  
1 Philips Parkway  
Montvale, New Jersey 07646-1810 USA.  
FAX: 201-476-7770

D8282584

## 16. Other information

**Revision comments** : Update as per OSHA GHS.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.