

# MATERIAL SAFETY DATA SHEET

SSS Carpet Spot Remover

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** SSS Heavy Duty Carpet Spot Remover  
**Product Number:** 05302  
**Product Use:** Spot Remover.  
**Manufacturer/Supplier:** Triple S  
2 Executive Park Dr.  
Billerica, MA 01862  
**Phone Number:** (978) 667-7900  
**D.O.T. Emergency Phone:** 1-(888) 779-1339  
**Date of Preparation:** August 8, 2007      **Revision #:** 1.0

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**HMIS:** See Section 15

DANGER

FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Eye:** May cause eye irritation.

**Skin:** May cause skin irritation.

**Ingestion:** Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

**Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, de-fatting and cracking of the skin.

**Medical Conditions Aggravated By Exposure:** Asthma. Allergies.

**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.

This product is a hazardous chemical as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment See Section 12 for more information.

# MATERIAL SAFETY DATA SHEET

SSS Carpet Spot Remover

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Isobutane	75-28-5	3 - 7
Propane	74-98-6	3 - 7
Isopropanol	67-63-0	5 - 10
Ethylene glycol monobutyl ether	111-76-2	1 - 5
Acetone	67-64-1	1 - 5
Alkyl polyglycosides	68515-73-1 / 110615-47-9	1 - 5
Dipropylene glycol methyl ether	34590-94-8	1 - 5
Propylene glycol phenyl ether	770-35-4	1 - 5

## Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Flammable by WHMIS/OSHA criteria.

**Means of Extinction:**

**Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

**Explosion Data:**

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

**Environmental Precautions:** Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

# MATERIAL SAFETY DATA SHEET

## SSS Carpet Spot Remover

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Clean-Up:** Allow gas to dissipate harmlessly into the atmosphere.

**Other Information:** Not available.

### Section 7: HANDLING AND STORAGE

#### Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

#### Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F.

### Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Isobutane	Not available.	Not available.
Propane	1000 ppm	1000 ppm
Isopropanol	400 ppm	200 ppm
Ethylene glycol monobutyl ether	50 ppm	20 ppm
Acetone	1000 ppm	500 ppm
Alkyl polyglycosides	Not available.	Not available.
Dipropylene glycol methyl ether	100 ppm	100 ppm
Propylene glycol phenyl ether	Not available.	Not available.

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

#### Personal Protective Equipment:

**HMIS:** See Section 15

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Clear.
<b>Color:</b>	White.
<b>Odour:</b>	Butyl.
<b>Odour Threshold:</b>	Not available.
<b>Physical State:</b>	Gas/Pressurized Liquid.

# MATERIAL SAFETY DATA SHEET

SSS Carpet Spot Remover

<b>pH:</b>	10-10.2
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	Not available.
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	Not available.
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	~ 60 (PSIG @ 70°F)
<b>Vapor Density:</b>	Not available.
<b>Specific Gravity:</b>	0.985 (Concentrate only)
<b>Solubility in Water:</b>	Partial.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Percent Volatile, wt. %:</b>	Not available.
<b>VOC content, wt. %:</b>	25% (US federal/CARB/OTC/LADCO)

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Oxidizers.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

<b>Ingredient</b>	<b>LD<sub>50</sub> (oral)</b>	<b>LC<sub>50</sub></b>
Isobutane	Not available.	Not available.
Propane	Not available.	Not available.
Isopropanol	5045 mg/kg, rat	16970 ppm 4 hrs, rat
Ethylene glycol monobutyl ether	470 mg/kg, rat	450 ppm 4 hrs, rat
Acetone	5800 mg/kg, rat	Not available.
Alkyl polyglycosides	Not available.	Not available.
Dipropylene glycol methyl ether	5400 uL/kg, rat	Not available.
Propylene glycol phenyl ether	2830 mg/kg, rat	Not available.

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

# MATERIAL SAFETY DATA SHEET

## SSS Carpet Spot Remover

- Skin:** May cause skin irritation. Symptoms may include redness, edema, drying, de-fatting and cracking of the skin.
- Ingestion:** Not a normal route of exposure. Harmful: may cause lung damage if swallowed.
- Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. This product may be aspirated into the lungs and cause chemical pneumonitis.

### EFFECTS OF CHRONIC EXPOSURE

- Target Organs:** Not available.
- Chronic Effects:** Not hazardous by WHMIS/OSHA criteria.
- Carcinogenicity:** Not hazardous by WHMIS/OSHA criteria.

<b>Ingredient</b>	<b>Chemical Listed as Carcinogen or Potential Carcinogen *</b>
Isobutane	Not listed.
Propane	Not listed.
Isopropanol	G-A4
Ethylene glycol monobutyl ether	Not listed.
Acetone	Not listed.
Alkyl polyglycosides	Not listed.
Dipropylene glycol methyl ether	Not listed.
Propylene glycol phenyl ether	Not listed.

\* See Section 15 for more information.

- Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.
- Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.
- Developmental Effects:**
- Teratogenicity:** Not hazardous by WHMIS/OSHA criteria.
  - Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.
- Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.
- Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.
- Toxicologically Synergistic Materials:** Not available.

### Section 12: ECOLOGICAL INFORMATION

- Ecotoxicity:** May cause long-term adverse effects in the aquatic environment
- Persistence / Degradability:** Not available.
- Bioaccumulation / Accumulation:** Not available.
- Mobility in Environment:** Not available.

### Section 13: DISPOSAL CONSIDERATIONS

- Disposal Instructions:**  
This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

### Section 14: TRANSPORTATION INFORMATION

**DOT Classification**  
ORM-D

# MATERIAL SAFETY DATA SHEET

SSS Carpet Spot Remover

## TDG Classification

Limited Quantity

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

### SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.
Isopropanol	Not listed.	Not listed.	Not listed.	Yes.
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.
Acetone	Not listed.	Not listed.	5,000	Not listed.
Alkyl polyglycosides	Not listed.	Not listed.	Not listed.	Not listed.
Dipropylene glycol methyl ether	Not listed.	Not listed.	Not listed.	Not listed.
Propylene glycol phenyl ether	Not listed.	Not listed.	Not listed.	Not listed.

### Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Isobutane	DSL	Yes.
Propane	DSL	Yes.
Isopropanol	DSL	Yes.
Ethylene glycol monobutyl ether	DSL	Yes.
Acetone	DSL	Yes.
Alkyl polyglycosides	DSL	Yes.
Dipropylene glycol methyl ether	DSL	Yes.
Propylene glycol phenyl ether	DSL	Yes.

### HMIS - Hazardous Materials Identification System

Health - 1      Flammability - 3      Physical Hazard - 0      PPE - B

### NFPA - National Fire Protection Association:

Health - 1      Fire - 3      Reactivity - 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

### WHMIS Classification(s):

Class A - Compressed Gas  
Class B5 - Flammable Aerosol  
Class D2B - Skin/Eye Irritant

### WHMIS Hazard Symbols:



# MATERIAL SAFETY DATA SHEET

SSS Carpet Spot Remover

## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

## Section 16: OTHER INFORMATION

### Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** August 8, 2010

**Prepared by:** Nexreg Compliance Inc.

**Prepared for:** Triple S

Phone: (978) 667-7900