MATERIAL SAFETY DATA SHEET

MSDS Number 332500FI

. PRODUCT AND COMPANY IDENTIFICATION

'roduct Name: FRAGRANCE OF THE ISLES AIR FRESHENER - ALL FRAGRANCES AND SIZES (30% VOC COMPLIANT)

lanufactured by:

Waterbury Companies, Inc.

24-Hour Emergency Contact:

P.O. Box 640

800-424-9300 or 703-527-3887

(CHEMTREC)

Independence, LA 70443 . COMPOSITION/INFORMATION ON INGREDIENTS

. COMPOSITION/INFORMATION ON INGREDIENTS **lazardous components greater than 1.0% (0.1% if carcinogen or suspected carcinogen)** **TMA 33-5356 **TMA 33-53566								
Component	CAS#	OSHA PEL	ACGIH TLV	Other Limits	% by wt.			
Acetone	67-64-1	1000 ppm	750 ppm	1000 ppm ACGIH STEL	35-45			
C8-C9 Isoparaffinic Hydrocarbons	64742-48-9	N.E.	N.E.	400ppm (Exxon)	<5			
Diethylene Glycol Monoethyl Ether	111-90-0	N.E.	N.E.	N.E.	25-35			
Perfume Oils-Supplier Trade Secret	N/A	N.E.	N.E.	N.E.	5-15			
⁻ropane	74-98-6	1000 ppm	1000 ppm	1000 ppm TWA	25-35			

. HAZARDS IDENTIFICATION

Varning! Flammable!

contents under pressure, do not expose to fire or extreme heat.

lead label. Use caution when installing; product contains an eye irritant. This product is designed for use in the Automatic Aerosol lispenser. One unit per 6,000 cubic feet should be considered as an average need. Keep in mind that factors such as air flow, size of ace, humidity, and room temperature all affect odor control. Do not allow spray to contact plastic, painted, or varnished surfaces.

'otential Health Effects:

Routes of Entry:

Inhalation: Yes

Ingestion: Yes

Skin: Yes

dealth Hazards: Acetone is irritating and possibly injurious to the eyes if not removed promptly. Acetone may increase the toxicity to the liver and kidney of chemicals such as ethanol, 1,2-dichloroethane, and chloroform. Humans with liver or kidney

disease may be at increased risks due to this potential effect.

igns/symptoms High vapor concentrations may cause upper respiratory tract irritation, narcosis (sleepiness, dizziness, etc.), and f overexposure: eye irritation. Prolonged skin contact may cause mild to moderate local redness and swelling. Contact with eyes may cause severe irritation, experienced as discomfort or pain, excessive blinking and tear production, with marked excess redness and swelling of the conjunctiva. Corneal injury may occur.

Medical conditions aggravated Skin contact may aggravate an existing dermatitis. y exposure:

IFPA Hazard Ratings

Fire:

4 Health:

Reactivity:

IFPA 704 Ratings are subject to interpretation and are only intended for general identification of the level of the specific hazard. All nformation must be considered for proper safe handling of the material.

. FIRST AID MEASURES

F IN EYES: Immediately flush with large amounts of water for at least 15 minutes. Do not remove contact lenses; obtain medical ttention immediately. IF ON SKIN OR CLOTHING: Remove contaminated clothing and wash before reuse. Wash affected areas of in with soap and water. Consult physician if irritation persists.IF INHALED: If large concentrations are inhaled, immediately move to esh air. Keep person calm. If not breathing, give artificial respiration. If labored breathing, give oxygen. IF SWALLOWED: Call a hysician or Poison Control Center immediately. Do not induce vomiting unless directed by medical personnel. Vomiting may cause spiration pneumonia hazard. Never induce vomiting or give anything by mouth to an unconscious person. Seek medical attention.

. FIRE FIGHTING MEASURES

extinguishing Media: Alcohol type or all-purpose foam for large fires, CO2 or dry chemical for small fires

Fire Fighting Procedures: Self-contained air supply suggested. Keep containers cool to avoid bursting. Water spray may be used to flush spills away from exposures.

Inusual Fire and Explosion Hazards: Exposure to temperatures above 120 deg. F. may cause bursting.

. ACCIDENTAL RELEASE MEASURES

container is ruptured or begins to leak, place in a well-ventilated area free of spark and ignition sources. Any remaining liquid should e collected with absorbent media. Dispose of unusable concentrate and absorbent media in accordance with Local, State and ederal regulations.

. HANDLING AND STORAGE

no not contaminate water, food or feed by storage or disposal. Store in a cool, dry area away from heat or open flame. Exposure to emperatures above 120 deg.F. may cause bursting. Do not install directly over any food handling or dispensing area. Do not store ear heat or open flame.

IFPA 30B Aerosol Classification:

Level 3 Aerosol

. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective Gloves: Not required - avoid contact with skin.

:ye Protection: Safety glasses recommended when installing new container to avoid possible contact with eyes.

evision Date 5/23/02 Date Printed: 11/7/02 Page 1 of 2

MATERIAL SAFETY DATA SHEET

MSDS Number 332500FI

Respiratory Protection:

Not required - avoid breathing spray.

'entilation:

Local: Not required.

Mechanical: Not required.

Other protective equipment:

Protective Work/Hygiene Practices: Follow label instructions.

. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (H2O=1): 0.73

Flashpoint: 60 deg. F (Tag Closed Cup).

LEL: N/A

'apor Pressure (mm Hg): 4,395

Boiling Point: N/A

Melting Point: N/A

UEL: N/A

Solubility: Appreciable

Appearance/Odor: Dry spritz with various characteristic fragrances.

0. STABILITY AND REACTIVITY

Conditions to Avoid: Heat, sparks, and open flame.

ncompatible Materials: Oxidizing materials, alkalis, acids, chlorinated compounds.

lazardous Decomposition By-products: May liberate Carbon monoxide, and carbon dioxide.

lazardous Polymerization Conditions: None known.

1. TOXICOLOGICAL INFORMATION

his product contains no chemicals that are listed on the NTP, IARC, or OSHA carcinogen lists. Any further information on the oxicology of the material can be obtained by contacting the manufacturer.

2. ECOLOGICAL INFORMATION

lease call the manufacturer for questions concerning the ecological effects of this product and it's constituents.

3. DISPOSAL CONSIDERATIONS

o not reuse empty container. This container may be recycled in the few but growing number of communities where (steel) aerosol n recycling is available. Before offering for recycling, empty the can by using the product according to the label. (DO NOT UNCTURE!) Any remaining or collected liquid from punctured cans should be disposed of in a safe manner at an approved facility in ccordance with Local, State, and Federal regulations. "Empty" cans may contain residue. Avoid exposure to heat, flame, sparks, and ther sources of ignition.

4. TRANSPORT INFORMATION

	Status	Shipping Name	Class	ID Numbe	Packing Gr
OT (USA):	Regulated	Consumer Commodity (per 49CFR173.306)	ORM-D	N/A	N/A
ATA (Air):	Regulated	Consumer Commodity	9	ID8000	N/A
MDG (Vessel):	Regulated	Aerosols	2	UN1950	N/A
lational Motor i	Freight Classification and L	TL Class: 57100 Sub 3 Class 60			

5. REGULATORY INFORMATION

ARA Title III Section 312: When completing Tier II reports, the following information should be used.

Note: See state and local regulations for specifics on reporting requirements for your facility.

his product should be described as: 'hysical Hazards: FIRE: Y

PURE: N

MIXTURE: Y

SOLID: N LIQUID: Y

GAS:

SARA Title III Section 313:

PRESSURE: Y REACTIVITY: N

N230

Health Hazards: IMMEDIATE: Y

DELAYED: Y

Chemical

6. OTHER INFORMATION

Toxic chemical components subject to the reporting requirements of EPCRA and 40CFR372: CAS/Category

Percent 25.00

Slycol Ethers

roduct Sales Information: 800-845-3495 ISDS Information: 985-878-6751

levision Notes: Annual review.

I/A = Not Applicable

N.E. = Not Established

MSDS Prepared by D.D.

his Information is provided in good faith, but no warranty, expressed or implied, is made. The manufacturer believes that it is occurate and to the best of its knowledge, and relates only to the specific material designated herein.

evision Date 5/23/02

Date Printed: 11/7/02

Page 2 of 2