



Pro Dryers

Ensure Spaces are Dry,
Safe and Ready for Use

POWERFUL AIR MOVERS

The CFR Pro Dryers provide up to 2500 CFM of powerful air movement for fast, complete drying of carpets, hard floors, office partitions or drywall. A three-speed control switch provides just the right air flow for properly timed drying cycles.

These units are perfect for controlled drying of carpets, fine rugs, hardwood floors, upholstery, use after fire, flood, water damage, or just general air circulation.

RUGGED CONSTRUCTION

Made of high density polyethylene housing, the Pro Dryers have molded cord wraps and handles for easy cord storage, handling, and multiple operating positions. Adjustable front legs allow you to dry out carpet down to the pad in record time. The DX versions goes even further and includes an expandable transport handle and wheels.

VERSATILITY

The Pro Series Dryers provide easy operation, versatility, innovative features and superior airflow for use in many different environments including:

- Hospitals and Healthcare Facilities
- Schools and Universities
- Hotels and Resorts
- Restaurants
- Commercial Office Buildings
- Retail Stores and Shopping Malls
- Industrial Facilities

Pro Dryer



Extra large inlets to increase airflow.

Molded-in stacking ribs allow for space-efficient storage.

Angle adjustment is a built-in feature of the Pro Dryer.

Place the unit flat for drying floors or at a 30 or 90-degree angle for drying walls or general air circulation.

KEY FEATURES

- Space saver stackable design
- Adjustable kickstand and 3 operating positions on model CFR 500
- Plastic injection molded inlets for maximum airflow - no rusting
- Molded, easy-carry handles for easy portability
- Rotomolded, high-density, polyethylene housing for rugged durability
- Extra large inlets to increase air flow



DX models include expandable, telescoping, transport handle and wheels.

PRODUCT SPECIFICATIONS

Model	CFR500	CFR500DX	CFR750DX
Power/Amp	4.8	4.8	4.8
Motor	1/2 hp	1/2 hp	3/4 hp
Speeds	3	3	3
Construction	Polyethyelene	Polyethyelene	Polyethyelene
Power Cord	20 ft.	20 ft.	20 ft.
Operating Positions	3 - positions	3 - positions	3 - positions
Handle	Molded, balanced	Molded, balanced	Molded, balanced
Transport Wheels & Handle	No	Yes	Yes
Inlets	Injection molded plastic	Injection molded plastic	Injection molded plastic
Sensors	Thermal shut-off	Thermal shut-off	Thermal shut-off
Warranty	1 Year	1 Year	1 Year
Weight	32.75 lbs.	32.75 lbs.	42 lbs.



CFR

Faster, Cleaner, Greener.

A Tacony Company
3101 Wichita Court
Fort Worth, TX 76140

Call Toll-Free 800.533.2557
www.CFRcorp.com
Form #: CFR 102 7/10