The Cimex Advantage...

Cyclone

CR /SC - Scrubber Polisher

The unique Cimex triple brush system means unbeatable performance, ease of use and increased operator safety

Applications

- · Scrubbing hard floors
- Polishing and cleaning of vinyl and ceramic floors
- Carpet cleaning
- Cleaning uneven surfaces e.g. studded rubber, tiles etc.
- · Grout line cleaning

Features and Benefits

- Unique Planetary motion provides deep cleaning action
- · Available in four sizes
- Floating brushes provide effective cleaning action of grout lines, slip resistant floors and textured natural stone
- Reversing brush action extends brush life
- Non-marking wheels for a truly professional finish
- Triple brush action prevents cable snagging
- Solution delivered through brush centers to reduce splashing
- Non-clog solution valve for uninterrupted operation
- Belt drive for quiet operation, ideal for hospitals, nursing homes and schools
- Extensive range of brushes available, covering all tasks from cleaning carpets or scarifying to polishing of hard floors
- No "bloom" rings or halo effects to mar floors
- Central motor for even brush pressure



Technical Specification				
Description	Cyclone 38	Cyclone 48	Cyclone 61	Cyclone 76
Model	CR38SC	CR48SC	CR61SC	CR76SC
Motor power (HP)	N/A	1.5	2.0	2.0
Pad/brush speed (rpm)	400	400	400	300
Working width (inches)	15	19	24	30
Pad/brush diameter (cm)	6.5	8	10	12
Pad brush pressure (oz./inch²/ Total lbs.)	10 / 84	10 / 104	7 / 132	6 / 174
Cable length (ft)	50	50	50	50
Solution tank capacity (US gallons)	6.6	6.6	6.6	6.6

We reserve the right to change specifications without prior notification.



Cyclone CR /SC - Scrubber Polisher

Cyclone scrubber/polishers are multi-purpose machines suitable for cleaning and polishing virtually every type of flooring from concrete to wood, vinyl to carpet or rubber to tiles.

A unique feature of Cimex rotary cleaning machines is the patented three-head mechanism, incorporating a counter rotating planetary system, which not only ensures a more thorough cleaning action, but also allows greater operational control with a torqueless action. This three-head system makes the operator's task much easier as it eliminates the tendency to "slide" which can be encountered with a single brush machine.

Technical Specification

Description	Cyclone 38	Cyclone 48	Cyclone 61	Cyclone 76
Model	CR38SC	CR48SC	CR61SC	CR76SC
Motor power (HP)	N/A	1.5	2.0	2.0
Pad/brush speed (rpm)	400	400	400	300
Working width (inches)	15	19	24	30
Pad/brush diameter (cm)	6.5	8	10	12
Pad brush pressure (oz./inch²/ Total lbs	.) 10 / 84	10 / 104	7 / 132	6 / 174
Cable length (ft)	50	50	50	50
Solution tank capacity (US gallons)	6.6	6.6	6.6	6.6
Motor height - clearance (inches)	16.5	18	19	22
Noise level (dB(A))	60	60	65	65
Weight (lbs.)	84	104	132	174
Length (inches)	29	32	47	50
Width (inches)	16	20	25	31
Height (cm)	44	44	44	44
Theoretical coverage: (m2/hr) Scr	Scrubbing	12285	19710	24570
	Polishing	23265	29520	36810
Spray Clean		11610	14760	18405
	Shampooing	15480	19710	24570

A complete range of brushes is available for carpet cleaning, scrubbing hard floors, cleaning quarry tiles and any dimpled or uneven floor surface.









