



*Equipment solid
to the KOR*

- Emissions Shut Down System
- Three-Way Catalytic Muffler
- Built To Meet GS-40 and LEED requirements
- Reusable Dust Bag
- Full Contact Weighted Pad Holder
- Produces Heat Required to Set Concrete Sealers, Guards, Densifier, and Impregnators

EnviroPro Series

STONEKOR LLC
 PO Box 443
 Adairsville, Ga 30103
 800.633.0519 toll free
 770.773.3875 local
 770.773.9903 fax
 www.stonekor.com



The EnviroPro Series increases floor temperature during burnishing so that the gloss level rises with use of densifiers. Built to meet GS-40 and LEED standards set for floor maintenance to capture dust and keep the working environment safe. This aluminum frame burnisher controls airborne debris with a unique air funnel system that traps and filters dust. Run time is 5 to 6 hours for one propane cylinder.

EnviroPro WB27, which while burnishing increases the floor temperature. The increase in Floor temperature increases the shine. This machine is great for concrete polishing with black or diamond pads. EnviroPro WB27 comes with a handheld infrared thermometer and a weighted metal pad driver.

Each machine comes standard with 360 degree floating swivel spin-on pad driver, Kill Switch, Emissions Shut Down System, adjustable handle, Tach O Meter, aluminum safety-fill fuel cylinder with overfill prevention device (OPD) UL and DOT approved, and limited two year warranty.

EnviroPro Series	EnviroPro WB27	EnviroPro 2700
Production	33,000 sq.ft.	33,000 sq.ft.
Engine Speed	3,450 rpm	3,450 rpm
Pad Speed	1,800 rpm	1,800 rpm
Pad Size	27 inches	27 inches
Box Dimensions	L 52 xW37.5xH46	L52 xW37.5xH46
Shipping Weight	350 lbs	350 lbs
<i>All STONEKOR equipment EPA and CARB certified for exhaust emissions.</i>		



Made in the U.S.A
 800.633.0519

