

Ouce Over,

NO RINSE STRIPPER

PRODUCT DESCRIPTION:

ONCE OVER[™] quickly penetrates through floor finish buildup and suspends the stripped finish for rinse free removal. Safe on most resilient and non-resilient floors that include mineral surfaces, terrazzo, concrete, vinyl, vinyl composition, asphalt, rubber, terrazzo, brick and quarry tile. Do not use on linoleum or tile that are in poor condition.

FEATURES:

No Rinse-No Machine:

Leaves no harsh alkaline residue that blocks the adhesion of the sealer or finish. Agitating the solution with a mop brings up the finish.

Efficient Finish Removal:

Quickly penetrates the finish and brings the finish into solution.

Non-ammoniated:

No ammonia odor. Reduces complaints while stripping the floor.

PRODUCT SPECIFICATIONS:

INGREDIENTS:

Water	7732-18-5
2-Butoxyethanol	111-76-2
Monoethanolamine	141-43-5
Sodium xylene sulfonate	1300-72-7
Ethylene glycol phenyl ether	122-99-6

ECOLOGICAL INFORMATION:

- Biodegradable Surfactants
- Contains No Phosphorus

1	DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
	CONCENTRATE CONCENTRAR	NFPA 3 HMIS	NFPA O HMIS	NFPA O HMIS
	(1:1 RATIO) (1:1 RAZON)	NFPA 3HMIS	NFPA O HMIS	NFPA O HMIS
	(1:4 RATIO) (1:4 RAZON)	NFPA 2HMIS	NFPA O HMIS	NFPA O HMIS
	PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD
	THOI ORGION	SILOD	INI EMMADIENDAD	RENOTIVIEND

0 1		2	3	4
Minimal	Slight	Moderate	Serious	Severe
Minimo	Minimo	Moderar	Grave	Drastico

Ince Over

NO RINSE STRIPPER

USE INFORMATION:

Before stripping always dust mop the floor and remove gum, labels and other attached soil deposits with a long handled scraper or putty knife.

FLOOR STRIPPING













CAUTION

1. DILUTE

3. WAIT

4. REMOVE

REPEAT

FLOOR STRIPPING

- 1. **DILUTE** at 32 ounces per gallon (1:4 ratio) of cool water. For heavy buildup, dilute 128 ounces per gallon (1:1 ratio) of cool water.
- 2. **APPLY** the diluted solution of **Once Over**TM onto the floor with a mop.
- 3. **WAIT:** Let stand for 4-5 minutes, then agitate with the same mop. For best results use a rotary machine and black pad. Do not let solution dry.
- 4. **REMOVE** the solution from the floor using a mop or wet dry vacuum. For best results rinse the floor with clean water and a clean mop.
- 5. **REPEAT** steps two to four if any finish remains on floor.

SPECIAL PRECAUTIONS: Not for use on linoleum, tile in poor condition, wood or painted surfaces or for daily maintenance of resilient tile floors. Before use on asphalt tile or rubber, test a small hidden area for any color change.

FIRST AID:

If in eyes or on skin, immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. If inhaled, remove to fresh air. Get medical attention. If swallowed, get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

HANDLING AND STORAGE:

SUGGESTED STORAGE TEMPERATURE: Store inside at 40-90°F. SPECIAL HANDLING AND STORAGE: Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. Protect from freezing. Thoroughly rinse empty containers. KEEP OUT OF REACH OF CHILDREN.

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.

Ventilation: Use with adequate ventilation.

Eye Protection: Safety goggles w/face shield required.

Protective Gloves: Safety gloves required.

Other Protective Clothing or Equipment: Wear clothing as

necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Ethanolamine Solution

Hazard Class: 8, Corrosive ID Number: UN 2491 Packing Group: III

Marine Pollutant: No

MSDS FAX RETRIEVAL Read MSDS before using this product 800-551-0101

OBTENCIÓN DE HDSM POR FAX Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY. SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
CALL CHEMTREC DAY OR NIGHT 800-424-9300

PARA EMERGENCIAS QUÍMIÇA DERRAMES, ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE LLAMAR DE DIA O DE NOCHE A CHEMTREC

TECH HOTLINE 800-810-4829 LINEA DE TÉCNICA