

# Super Gard™

## UNDERCOATER SEALER

**PRODUCT DESCRIPTION:**

**Super Gard™** represents a "modern concept" in acrylized emulsion polymer chemistry. It is a major breakthrough in reference to the total undercoater/sealer protection of all resilient and non-resilient floors, with the exception of unsealed wood floors. **Super Gard™** is formulated with metalized acrylic polymers, thereby achieving unusual levels of durability and permanency. **Super Gard™** is an excellent choice where protection from salt exposure is required.

**FEATURES:**

**Super Protective Coating:**

**Super Gard™** is salt resistant and has outstanding black heel mark and scuff resistance properties.

**Exceptional Stain Resistance:**

**Super Gard™** prevents stains from setting into the floor. The floor is protected from oil, rust, betadine and other soils.

**Non-Yellowing:**

**Super Gard™** is a water-based system with no waxes or resins to cause darkening or yellowing.

**Easy and Economical:**

No foaming or streaking even under high humidity conditions. Increases the coverage of top coating.

**PRODUCT SPECIFICATIONS:**

pH	8.8 ± 0.5
Appearance	White Emulsion
Fragrance	Polymeric
Freezing Point	About 32°F
% Solids	16.3 ± 0.3
Boiling Point	212°F
Solubility in Water	Complete
Flash Point	None
Coverage	1700 to 2000 sq. ft. per gallon (may vary due to differences in porosity of the surface)

**Slip Resistance:** Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

**INGREDIENTS:**

Water	7732-18-5
Styrene acrylate copolymer	25987-66-0
Styrene acrylate copolymer	28263-96-9
Ethylene glycol	107-21-1
Diethylene glycol ethyl ether	111-90-0

DILUTIONS	HEALTH	FLAMMABILITY	REACTIVITY
CONCENTRATE	NFPA 1	HMIS 0	NFPA 0
CONCENTRAR			
PROPORCIÓN	SALUD	INFLAMABILIDAD	REACTIVIDAD

0	1	2	3	4
Minimal	Slight	Moderate	Serious	Severe
Mínimo	Mínimo	Moderar	Grave	Drástico

DATA SHEET

# Super Gard™ UNDERCOATER/SEALER

# DIRECTIONS

## USE INFORMATION

*Super Gard™ is recommended for use on vinyl composition, vinyl asbestos, vinyl, asphalt, linoleum and rubber floors. May be used on nonresilient surfaces that are not glazed. These surfaces include concrete, terrazzo, quarry tile, Mexican tile, brick, marble, slate and other nonresilient floors.*

### INITIAL APPLICATION




CAUTION



1. REMOVE



2. APPLY




3. DRY  
20-30



4. FINISH

### MAINTENANCE



1. DUST MOP



2. MOP

### INITIAL APPLICATION

1. **REMOVE** old sealer or finish following label directions using a Franklin stripper.
2. **APPLY** one or two coats of **Super Gard™** using a clean finish mop and a bucket.
3. **DRY:** For best results allow adequate drying time between each coat.
4. **FINISH:** Apply 2-3 additional coats of a Franklin floor finish. For best results allow adequate drying time between each coat.

### MAINTENANCE

1. **DUST MOP** the floor. Remove gum, labels and other attached soil deposits with a long handled scraper or putty knife.
2. **DAMP MOP OR AUTOSCRUB** using a Franklin cleaner and following the label directions.

### FIRST AID:

If in eyes or on skin, immediately flush with plenty of water. Get medical attention. If swallowed, get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

### HANDLING AND STORAGE:

**SUGGESTED STORAGE TEMPERATURE:** Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool and dry ventilated area. **Protect from freezing.** Thoroughly rinse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

### PERSONAL PROTECTION:

**Respiratory Protection:** Not needed in normal use of this product.  
**Ventilation:** Use with adequate ventilation.  
**Eye Protection:** Safety glasses are optional.  
**Protective Gloves:** Protective gloves are optional.  
**Other Protective Clothing or Equipment:** Wear clothing as necessary to prevent skin contact.

### TRANSPORTATION INFORMATION:

**U.S. DOT - Proper Shipping Name:** Not regulated by DOT.  
**Marine Pollutant:** No

MSDS FAX RETRIEVAL  
Read MSDS before using this product

**800-551-0101**

OBTENCIÓN DE HDSM POR FAX  
Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY,  
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT  
CALL CHEMTREC DAY OR NIGHT

**800-424-9300**

PARA EMERGENCIAS QUÍMICA DERRAMES,  
ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE  
LLAMAR DE DÍA O DE NOCHE A CHEMTREC

**TECH HOTLINE**

**800-810-4829**

**LINEA DE TÉCNICA**