

# Product Specifications

## 3M™ High Productivity Pad 7300

### 1.0 Product Description

This product is a floor maintenance stripping pad made of continuous filament nylon in an open textured non-woven construction. Abrasive particles are disbursed throughout and bonded to the non-woven construction with a durable adhesive. The pads are nominally one-half inch thick.

### 2.0 Intended Use

The pad is used with water-based floor finish stripping solutions to remove old soiled floor finishes and sealers. The product is normally used on low speed rotary floor machines or automatic scrubbers.

### 3.0 Standard Sizes

Circular discs and other shapes are available in a variety of common sizes.

### 4.0 Color

Black

### 5.0 Requirements:

#### General Requirements:

This product shall be made of continuous filament nylon fiber bonded with synthetic adhesives and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The abrasive cleaning particles shall be made of synthetic materials.

#### Detailed Requirements

Typical Properties:

<u>Property</u>	<u>Value</u>	<u>Test Method</u>
O.D. Dimension	Designated size ± 1/16 inch	SB 61
Thickness	1/2 inch nominal	SB 66
Weight (4 in. x 6 in.)	22 g	
Fiber type	Continuous filament nylon	
Fiber size	500 denier	
Average tensile strength	42 lbs./2 in.	SB 6.4
Aggressiveness (cut)	3.5 g	SB 3.0
Average mineral weight (4 in. x 6 in.)	15 g	
Recycle content of packaging	Not less than 35% post-consumer recycled material	

## **6.0 Packaging and Marking**

**Packaging:** 5 pads per case

**Marking:** Each carton shall be labeled to identify the contents by product name, size and manufacturer. Each pad shall be printed with manufacturer's name.

## **7.0 Pad Use and Cleaning**

Directions for Use:

Dust mop or sweep floors prior to scrubbing with a water-based floor finish stripping solution and the High Productivity Pad. Pick up dirty stripping solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry before recoating.

Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked-on soil or finish prior to cleaning.

### **Important Notice:**

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



### **Building and Commercial Services Division**

St. Paul, MN 55144-1000

1-800-852-9722

[www.3M.com/commcare](http://www.3M.com/commcare)

3M is a trademark of 3M.

©3M 2007