

Product Specifications

3M™ Black Stripper Pad 7200

1.0 Product Description

This product is a floor maintenance stripping pad made of nylon and polyester fibers in an open textured non-woven construction. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable adhesive. The pads are nominally 3/4 inch thick and available in various sizes.

2.0 Intended Use

The product is used with water-based floor finish stripping solutions to remove old soiled floor finishes and sealers. The product is also used to clean heavily soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. The product is normally used on low speed rotary floor machines or automatic scrubbers.

3.0 Standard Sizes

Circular discs and other shapes are available in a variety of common sizes.

4.0 Color

Black

5.0 Requirements:

General Requirements:

This product shall be made of nylon and polyester fibers and synthetic adhesives and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The abrasive cleaning particles shall be a mixture of natural and synthetic materials.

5.0 Requirements (continued)

Detailed Requirements

Typical Properties:

| <u>Property</u> | <u>Value</u> | <u>Test Method</u> |
|--|---|--------------------|
| O.D. Dimension | Designated size ± 1/16 inch | SB 61 |
| Thickness | 3/4 inch nominal | SB 66 |
| Weight (4 in. x 6 in.) | 30.5 g | |
| Average mineral weight (4 in. x 6 in.) | 17 g | SB 1.5 |
| Fiber type | Nylon/polyester blend mixture of sizes | |
| Average tensile strength | 60 lbs./2 in. | SB 6.4 |
| Alkali Resistance (Tensile Retention) | 99% | SB 1.6.3 |
| Aggressiveness | 3.6 g | SB 3.0 |
| Aggressiveness Retention | 70% | SB 3.0 |
| Wear (weight loss) | 22% | SB 2.0 |
| Recycle content of packaging | Not less than 35% post-consumer recycled material | |

6.0 Packaging and Marking

Packaging: 5 pads per case

Marking: Each carton shall be labeled to identify the contents by product name, size and manufacturer. Each pad shall be printed with manufacturer's name.

7.0 Pad Use and Cleaning

Directions for Use:

Dust mop or sweep floors prior to scrubbing with stripping or cleaning solution and floor pad. Pick up dirty solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked on soil or finish prior to hosing out.

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



Building and Commercial Services Division

St. Paul, MN 55144-1000

1-800-852-9722

www.3M.com/commcare

3M is a trademark of 3M. © 3M 2007.