

# Product Specifications

## 3M™ Brown Stripper Pad 7100

### 1.0 Product Description

This product is a floor maintenance stripping pad made of nylon and polyester fibers in an open textured non-woven construction. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable adhesive. The pad is nominally one inch thick and is made in various sizes.

### 2.0 Intended Use

The pad is used with water based floor finish stripping solutions to remove old soiled floor finishes and sealers. The product is also used to clean heavily soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. The product is also used for dry stripping floors using minimum moisture content stripping chemicals.

### 3.0 Standard Sizes

Circular discs and other shapes are available in a variety of common sizes.

### 4.0 Color

Brown

### 5.0 Requirements:

#### General Requirements:

This product shall be made of nylon and polyester fibers and synthetic adhesives and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The abrasive cleaning particles shall be of synthetic material. The product shall be reversible and nominally one inch thick.

#### Detailed Requirements

##### Typical Properties:

<u>Property</u>	<u>Value</u>	<u>Test Method</u>
O.D. Dimension	Designated size ± 1/16 inch	SB 61
Thickness	1 inch nominal	SB 66
Weight (4 in. x 6 in.)	27.3 g	
Average mineral weight (4 in. x 6 in.)	14.6 g	SB 1.5
Fiber type	Natural/polyester blend mixture of sizes	
Average tensile strength	53 lbs./2 in.	SB 6.4
Agressiveness	2.0 g	SB 3.0
Wear (weight loss)	30%	SB 2.0
Recycle content of packaging	Not less than 35% post-consumer recycled material	

## **6.0 Packaging and Marking**

**Packaging:** 5 pads per case

**Marking:** Each carton shall be labeled to identify the contents by product name, size and manufacturer. Each pad shall be printed with manufacturer's name.

## **7.0 Pad Use and Cleaning**

Directions for Use:

Dust mop or sweep floors prior to stripping. Pick up stripping or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked-on soil or finish prior to cleaning.

### **Important Notice:**

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

**3M**  
**Building and Commercial Services Division**

St. Paul, MN 55144-1000

1-800-852-9722

[www.3M.com/commcare](http://www.3M.com/commcare)

3M is a trademark of 3M. © 3M 2007.