

CLEANMASTER™ FLOOR MACHINE

POWERFUL STRIPPING, SCRUBBING AND POLISHING

Operate this dual-speed floor machine
at either 175 or 300 RPM!

Private Label
Branding
Available!



Precision Balanced
All Metal Chassis
High Torque
Interlock Switches
Heavy-Duty
Safe & Easy to Use

POWERFUL. SAFE. EASY TO USE.

LABOR SAVING SPEED FROM MERCURY FLOOR MACHINES!

The Cleanmaster Floor Machine from Mercury offers the versatility of two machines in one, operating at dual speeds! The powerful precision-balanced, 1.5 HP 66-frame D/C rectified motor eliminates brown-outs, low voltage and startup torque problems for fast, easy scrubbing.



CLEANMASTER™ FLOOR MACHINE

by Mercury Floor Machines



Manufactured with
Pride in the U.S.A.

SEE THE BENEFITS

of the Cleanmaster Floor Machine from Mercury

- Powered by a precision-balanced, 1.5 HP 66-frame D/C rectified motor with triple-planetary gears. Eliminates brown-outs, low voltage and startup torque problems for fast, easy scrubbing.
- 175/300 RPM dual-speed brush – the versatility of two 1.5 HP machines in one!
- The all-metal, balanced chassis provides more precise pad pressure and beautiful results. It's easy to clean and looks newer longer.
- Choose from 17", 19" or 21" all metal bell housing aprons.
- Scrub with a brush 2" smaller than the apron size, or a pad and pad driver 1" smaller than the apron size. Easy brush mounting with a "B"/"92" style brush drive plug.
- 6" non-marking, fixed operating wheels for easy transport.
- Safety-enhanced interlock switch on the handle leaves both hands conveniently in control.
- Safety-enhanced, non-conductive dual triggers on the handle eliminate shock potential. It includes heavy-duty dual switch levers.
- Fully adjustable 48" handle is comfortable for all operators.
- Non-marking super-thick bumper protects walls and baseboards.
- Includes (1) 50-foot, 14/3-gauge safety power cord. Motor plugs into this cable at the base of the handle. Maintenance is safe and easy.



Specifications:

CLEANMASTER DUAL-SPEED FLOOR MACHINE

Model Number:	TS-17	TS-19	TS-21
Machine Size:	17"	19"	21"
Rotary Brush:	15"	17"	19"
Rotary Pad Driver w/ Riser:	16"	18"	20"
Shipping Weight:	102 lbs.	103 lbs.	104 lbs.
Motor Type:	1.5 HP, 66-Frame D/C Rectified Motor, 13-15 Amps		
Brush Speed:	175/300 RPM Dual-Speed		
Brush Drive:	"92" Style, "B" Style Drive Plug and Clutch Plate		
Chassis:	Polished Aluminum		
Powder Cord:	(1) 50-Foot, 14/3-Gauge Safety Power Cord		
Wheels:	6" Non-Marking Wheels		
Warranty:	5-Years on Motor, Transmission and Chassis		



**CALL US TODAY IF YOU HAVE ANY QUESTIONS,
OR WOULD LIKE TO PLACE AN ORDER!**

110 South Van Brunt Street, Englewood, NJ 07631
(p) 888-568-4606 | (f) 201-568-7962 | www.mercuryfloormachines.com