



2200 Mytee-Dry™

Airmover



PRODUCT SPECIFICATIONS

Motor	1/3 horsepower - 4 amps at 115 volts
Operating Speeds	Low (1800 CFM), Medium (1950 CFM), High (2200 CFM)
Power Cords	Single 25' 14/3
Housing	Roto-molded polyethylene
Dimensions	20" x 17" x 18"

Get it Mytee-Dry™

Reduce profit-stealing drying time and increase convenience and efficiency with our powerful adjustable airmover. Unique features let you control airflow to match the job, whether drying surfaces, delicate carpets or upholstery.

POWER

A powerful three speed motor for maximum versatility, at the highest speed setting has an output of 2200 CFM.

EFFICIENCY

Requires only 4 amps at 115v. Run more blowers on each job, to improve drying times.

DURABILITY

The rugged roto-molded polyethylene housing is the most durable in the industry. In fact, we are so confident of this, the housing is covered by a lifetime factory warranty!

CONVENIENCE

It is stackable for storage and features built in cord wrap. An optional transport handle package is also available.

VERSATILITY

Designed to be used in three different drying positions to dry walls, ceilings, carpets, floors, and more.

- 1 INTERLOCKING HANDLE
- 2 ON BOARD CORD WRAP
- 3 THREE OPERATING SPEEDS
- 4 INDUSTRY'S STRONGEST HOUSING
- 5 OPTIONAL TRANSPORT HANDLE W/ WHEELS



At Mytee, we stand behind our products with service and warranties. The 2200 Mytee-Dry™ is backed by a lifetime limited factory warranty and nationwide service network.