

Wrangler® 1708/2008

Compact Automatic Scrubbers



Ergonomic design, simple operation and a compact body make the Wrangler 1708 and Wrangler 2008 the best values in small scrubbers.

- Designed for applications from 10,000 to 30,000 square feet, these Wranglers are perfectly sized for small office buildings, convenience stores, and nursing homes. They are also ideal for larger facilities with confined areas, such as grocery store checkout aisles, school cafeterias, commercial kitchens, and hospital rooms.
- Wrangler compacts feature an 8-gallon solution tank and an oversized 10-gallon recovery tank, which allows room for foam, helping protect the vacuum motor from moisture.
- The 32-inch straight squeegee features a breakaway assembly to prevent damage when it inadvertantly catches on any fixed object. Reconnecting is as simple as hand tightening two control knobs.
- To simplify pad changing, a foot latch at the front of the machine allows the body to tilt up and back. This also provides easy access to the batteries and all internal components.
- Wrangler compacts are available with a 17-inch or 20-inch scrubbing path in either battery-powered (AB) or cord-electric (AE) models.
- The on-board charger, standard on all battery-powered Wrangler automatic scrubbers, allows the batteries to be charged anywhere an electrical outlet is available.

NSS® Enterprises, Inc. 3115 Frenchmens Road Toledo, Ohio 43607-2958 USA www.nss.com



Battery-Powered Wrangler 1708/2008 AB Specifications

Brush/Pad

1708 17 in (43 cm) 2008 20 in (51 cm)

Pad Drive Motor

Type Permanent magnet, 24V, 0.75 HP

Speed 270 RPM

Vacuum Motor

Type 2-stage bypass peripheral discharge

HP 0.5 HP

CFM 65.1 (1.8 m³)
Waterlift 49 in (124 cm)

Power Two 12V, 115 AH

Batteries Two 12V, 115 AH

Tank Capacity

Solution 8 gal (30L) Recovery 10 gal (38 L)

Squeegee 32 in (81 cm) swing type with

breakaway feature; picks up in

forward and reverse

Construction

Body Rotocast polyethylene tanks and body, hinged on steel frame

Wheels Two 8 in (20 cm) non-marking

wheels

Casters Two front 3 in (7.6 cm) ball-bearing

swivel casters

Float Ball Type

Sound Level 66 dBA @ operator

Dimensions

Length 44.5 in (113 cm)
Width 1708 19 in (48 cm)
Width 2008 21.5 in (55 cm)
Body Height 30.5 in (77.5 cm)

Handle Height 40.5 in (103 cm)

Weight

Machine 1708 AB 345 lbs (156.5 kg)
Machine 2008 AB 347 lbs (157.5 kg)
Shipping 1708 AB 383 lbs (173.9 kg)
Shipping 2008 AB 387 lbs (175.7 kg)

Shipping Class 125

Warranty 3 year limited, 10 years poly parts

Productivity

1708 AB 12,739 sq ft (1,183 m²) per hour 2008 AB 14,960 sq ft (1,390 m²) per hour



NSS Enterprises, Inc. 3115 Frenchmens Road Toledo, OH 43607-2958

P: (800) 677-1663 F: (419) 531-3761

mailus@nss.com www.nss.com Specifications subject to change without notice.





The steel frame is recycleable, reducing this Wrangler's environmental footprint.

Pad rotation assists with machine propulsion, reducing operator fatigue.

The quiet operation (66 dBA) allows extended use in daytime cleaning environments.

- The ergonomic handles provide increased control while reducing operator fatigue.
- 2 Clear-view top port cover permits operator to easily monitor solution recovery.
- **3** 8-gal solution tank and 10 gal recovery tank for increased productivity.
- 4 The on-board battery charger allows recharging anywhere an outlet is available.
- 6 Rotocast polyethylene body is dent-resistant and durable, backed by a 10-year warranty.
- **(3)** Two 12V 115 AH batteries power the vacuum and brush motors on the cordless models. The PROeye battery fluid indicator lets the operator easily monitor when a battery needs water.
- 7 Two 8 in rear wheels and swivel front casters make the Wrangler 1708/2008 extremely maneuverable.
- **3** The oversized 32 in squeegee picks up in forward and reverse, swinging wide on turns to recover all solution.

Cord-Electric Wrangler 1708/2008 AE Specifications

Vacuum Motor 2-stage bypass peripheral discharge, 1.25 HP, 115V, 92 (2.6 m³) CFM, 84 in (213 cm) waterlift

Power 75 ft (22 m) 14-3 cord

Pad Drive Motor Permanent magnet, 120V, 0.75 HP, 250 RPM

Weight

Machine 1708 AE 233 lbs (106 kg)
Machine 2008 AE 235 lbs (107 kg)
Shipping 1708 AE 271 lbs (123 kg)
Shipping 2008 AE 275 lbs (125 kg)

DISTRIBUTED BY

Printed in USA ©2009 NSS Enterprises, Inc.

#9091301 REV F 5/09