



Maverick 300

Variable-Speed Floor Machine



For versatility in floor and carpet care, the Maverick 300 sets the standard for variable-speed floor machines. By dialing the appropriate speed, the Maverick 300 will polish, spray buff, scrub, and strip.

- A powerful 1.5 HP motor assures excellent performance at any speed between 200 and 310 RPM.
- At lower speeds, the Maverick 300 is the ideal machine to rotary scrub hard floors and carpeted areas. Lower pad speeds are also recommended when using the Maverick 300 to wet strip hard floors.
- The highest pad speed—310 RPM—will buff or spray buff hard floors or bonnet clean carpet.
- The Maverick 300, available in 17-inch (43.2 cm) and 20-inch (50.8 cm) widths, includes a lock-out mechanism on the handle. This safety feature helps to prevent unauthorized use of the machine.

NSS® Enterprises, Inc.
3115 Frenchmens Road
Toledo, Ohio 43607-2958
USA
www.nss.com



Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

Maverick 300 Specifications

Pad or Brush	17 in (43.2 cm), 20 in (50.8 cm)
Motor	
Type	Permanent magnet, DC rectified
HP	1.5 HP (1100 watts)
Size	66 frame
Voltage	110-120V (220-240V available)
Current	15 amps@ 120V, 7.5 amps @ 240V
Gear	3-idler planetary, 10:1 ratio
Pad Speed Variable between:	
High	310 RPM
Low	200 RPM
Cord	75 ft (23 m) 16-3 ST SHUKO safety yellow
Dimensions	
Length	26 in (66 cm)
Width	22 in (56 cm)
Height	49 in (124 cm)

Weight (w/ Pad Driver)

17 in Machine	85 lbs (38.6 kg)
20 in Machine	92 lbs (41.8 kg)
17 in Shipping	113 lbs (51.3 kg)
20 in Shipping	120 lbs (54.5 kg)

Shipping Class

Warranty 3 year limited

Productivity (17 in)

Polish	7,000 sq ft per hour (650 sq m)
Scrub	2,700 sq ft per hour (251 sq m)
Shampoo	1,200 sq ft per hour (111 sq m)
Spray Buff	2,700 sq ft per hour (251 sq m)

Productivity (20 in)

Polish	10,000 sq ft per hour (929 sq m)
Scrub	3,600 sq ft per hour (334 sq m)
Shampoo	1,430 sq ft per hour (133 sq m)
Spray Buff	3,100 sq ft per hour (288 sq m)



The variable-speed control switch allows the operator to match the pad speed with the job at hand.



The Maverick 300 sports a unique pad driver, which is balanced to provide smooth operation.



- ❶ The Maverick 300 control handle includes a mechanical lock-out which must be released before the switch lever can be activated.
- ❷ Dual switch levers allow the operator to easily control the side-to-side movement.
- ❸ Metal cord strain relief and internal compression lock prevent the cord from being pulled out of the machine.
- ❹ Sturdy 1.5-in tube handle is chrome-plated to resist corrosion.
- ❺ Built-in cord wrap hook provides easy storage for the power cord when not in use.
- ❻ Locking lever lets operator adjust handle to comfortable position.
- ❼ 360° non-marking bumper protects walls and fixtures from accidental damage.



Variable-speeds allow the machine to be used at the speed required to do the job, eliminating wasted effort and energy.

5-in rear transport wheels make the Maverick 300 easy to move from job-to-job.

The handle and deck on this machine is recycleable, lessening the environmental footprint of this scrubber.



NSS Enterprises, Inc.
3115 Frenchmens Road
Toledo, OH 43607-2958
USA

P: (800) 677-1663
F: (419) 531-3761

mailus@nss.com
www.nss.com

Specifications subject to change without notice.

DISTRIBUTED BY