## UL Rated 4-A, 60-B:C



## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 460 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from impact resistant steel and the valve assembly is all aluminum.

Features bilingual nameplate and carton.

## FOR HIGH HAZARDS

#### **Features**

- **Multipurpose Fire** Extinguisher
- Steel cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit
- Assembled in Mexico from global components
- 6 year warranty
- UL rated 4-A, 60-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with optional mounting bracket
- Optional metal strap bracket Pt # 366242
- Powder coated cylinder for corrosion protection



Pt # 21005785 - 2 pack UPC: 0-47871-05785-6 I2F - 10047871057853

## For use on the following types of fire:









# Product Specification

rioduct specification				
Net agent weight (Average)	10 lb.			
Unit weight (Average)	17 lb.			
Diameter	5.21 inches			
Height	19.52 inches			
Discharge time	19-21 seconds			
Discharge range	20-25 feet			
Operating pressure	195 psi			
Cylinder	Steel			
Valve/handle/lever	Aluminum			
Strap Bracket (not supplied)	U.S.C.G approved			

## Packaging Options



Packaging dimensions (inches)

_	4				
		Depth	Width	Height	
	Carton	5.37	6.62	19.5	
	Master Pack	14.37	21.0	5.81	