



Product Technical Sheet

SSS CONTACT & CIRCUIT BOARD CLEANER V

Description: Developed for the Electronics, Healthcare, Communications and Media, Aeronautical and Electronics Servicing industries. Removes oil, dirt, condensation and moisture from circuit boards, precision instruments, oxygen equipment, controls, switches, and electrical motors. Approved for short-term contact (normal aerosol light spray use) on a wide variety of component plastics. including: Acetal, Neoprene, Nylon, Polyethylene (HDPE), Polyphenylene Sulfide (PPS), Polypropylene (copolymer), Polysulfone, Teflon, Viton. Leaves no residue and is compatible with many component metals including most types of steel, galvanized steel, brass, copper, magnesium, nickel, tin plate, titanium, zinc, etc. 16 ounce can.

Directions: Always test in an inconspicuous area before general use. Do not use on styrene or polystyrene.

GENERAL APPLICATION: For the cleaning of fairly large surfaces, aim the spray tip at the area to be cleaned and press button. For the cleaning of confined areas and small exact spots, insert the 4" plastic extension tube into the valve opening until it bottoms, then spray.

Health Hazard Data: Contains 1-Bromopropane. Eye and skin irritant. Avoid contact with skin and eyes. If eye contact occurs, flush with water for 15 minutes. If irritation persists, consult a physician. If skin contact occurs, remove contaminated clothing. Wash with soap and warm water. If irritation persists, consult a physician. Vapor may be harmful. May irritate respiratory tract. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapors. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Avoid contamination of food. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN.**

Spill Or Leakage Procedures: Do not flush to sewer. Absorb with suitable material and dispose of according to local, state and federal regulations. Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Product Specifications:

Wt./16oz. can:	14 Net Weight Ounces
USDA Category:	N/A
Classification:	Aerosol Contact & Circuit Board Cleaner
General Appearance:	Clear
Color:	Colorless
Odor:	Solvent
pH:	N/A
Vapor Pressure At 70°F:	50 – 60 psig