

PRO SERIES

THERMOFORCE

UHS FLOOR RESTORER

UHS RESTAURADOR DEL PISO



Technical Data

Areas of Use

- Classrooms
- Healthcare facilities
- Office buildings
- Hallways
- Entrances
- Hospitals
- Vinyl Tiles
- Linoleum
- Terrazzo
- Quarry Tile
- Slate
- Concrete

Specifications

SSS Item Numbers...48170, 48171, 48172, 48173
 Available Sizes.....1G, 2.5, 5G, 55G
 Physical State.....Liquid
 ColorTranslucent Opal Green
 FragranceMild Citrus
 Specific Gravity.....1.018
 pH8.0 -9.0
 Detergency.....Excellent
 Viscosity.....Water Thin
 Slip Resistance.....Improves Traction
 Flash Point.....None
 Solubility.....Complete with water
 Storage/Stability1 year
 Weight Per Gallon8.50 lbs./gal.
 Freeze/Thaw StabilityKeep from freezing

HMIS Hazardous Materials I.D. System

Health1
 Flammability0
 Reactivity0
 Personal ProtectionA

What the Pros Know

- Excellent leveling properties, fills in scratches
- Mops on clear, does not yellow floor finish
- Low end use cost
- Less exposure to slip and falls
- Ultimate wet look shine

Description

A one-step cleaner and restorer that is an ideal companion product for use with NANOFORCE floor finish as well as other acrylic finishes. The nano additive provides excellent leveling properties, “wet look” gloss, and does not yellow. The “liquid thermoplastic polymer” resists powdering caused by the heat and friction generated with a high-speed burnisher while improving traction. Thermoformce will not trap soil and is highly concentrated for economical use. Can be used in automatic scrubbers or in mop and bucket applications.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



FOR HEAVY RESTORING:

1. Dust mop all flooring and remove any gum or adhesives.
2. Damp mop or auto-scrub floor with a neutral pH floor cleaner following label directions.
3. Dilute 1 part restorer to 4 parts cool water in a mop bucket or automatic scrubber.
4. Apply a thin, even coat with a clean mop or automatic scrubber to the surface. Do not pickup solution. Allow to dry thoroughly.
5. Burnish all flooring to restore the floor to the ultimate “wet looking” shine.

FOR LIGHT RESTORING USING AN AUTO-SCRUBBER:

1. Dust mop all flooring and remove gum and adhesives.
 2. Dilute 1 part restorer to 16 parts cool water in the solution tank of the automatic scrubber
 3. Auto-scrub all flooring using overlapping passes while dispensing, agitating, and picking up the solution. 4. Pick up any puddles with a clean damp mop. Allow to dry thoroughly.
 5. Burnish all flooring to restore the floor to the ultimate “wet looking” shine.
- Note: Don't allow restorer solution to remain in the auto-scrubber tank. Drain and rinse. This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by current State and Federal regulations.

Excellent Leveling

Does Not Yellow Floor Finish

Low End Use Cost

