

Product Specifications

Puma G 3-Speed, Transportable Air Mover



Item No.	86022
Motor	.33 hp
Speed	3 speeds
Air Flow (C.F.M.)	Low: 1,700 Med: 2,100 High: 2,400
Fan Diameter	9.75"
Amp Draw	Low: 5 Med: 5.3 High: 5.8
Housing Construction	Durable Injection-molded polypropylene
Fan Construction	Injection-molded
Angle Positions	3 = 0°, 20°, & 90°
Swing-out Kickstand	Provides an extra 20° position
Sound Level (dBA)	Low: 64 Med: 68 High: 72
Power Cable w/Cord Wrap	22' or 25' Safety Orange
Built-in Wheels	(2) 3.5"
Built-in Handle	Adjustable, Telescopic
Two GFCI Outlets	Safely plug 3 units into each other to
	dry large areas
Weight / Shipping Wt.	23.6 lbs. / 28.4 lbs.
Dimensions	17L x 16W x 16.5H inches

Specifications are subject to change without notice.

The SSS Puma G 3-Speed, Transportable Air Mover provides a powerful source of air for drying carpet, hard floors and for additional ventilation. Three angle positions and two GFCI outlets connect up to 3 units making it especially useful in drying out after floods or large areas. The 3-speed switch lets you set the air flow to your specific needs. Complete with built-in wheels, a telescopic, easy grip handle and cord wrap, for easy transportation. Stack up to 4 units for storage. The Puma G is engineered for heavy, daily use at schools, offices, auto detailers, construction sites, flood restoration areas, and more.