



# Ultron 20BA / Ultron 20TD

Automatic Scrubber



**Better Cleaning. Better Performance. Better Results.**

# Ultron 20BA / Ultron 20TD

## Automatic Scrubber



66 or 100 pounds pressure for a variety of scrubbing applications



Easy to understand controls

Durability and ergonomics are the hallmarks of the 20BA and 20TD automatic scrubbers. Clean and scrub all types of hard surfaces including resilient tile, ceramic, wood stone, concrete and more. Choose between the brush assist (20BA) or transaxle drive (20TD) based on your needs and budget. The brush assist drive system makes it easy to move the machine forward with little effort, or let the transaxle drive handle it. Quiet operation lets you clean anytime without interrupting others.

### Benefits:

- Intuitive, ergonomic controls for simple operation.
- Large 15-gallon solution tank improves working efficiency.
- Two pad pressure settings for flexible cleaning.
- On-board charger, 19" pad driver, and squeegee assembly included.
- Traction-drive or pad-assist drive based on facility needs.
- Filter assembly and auto-float shutoff protects vacuum motor.
- Heavy-duty die-cast aluminum brush deck.
- No tools required for changing curved squeegee blades.
- 5 YEAR WARRANTY on all parts and labor with the exception of "wearables" such as brushes, pad drivers, batteries, hoses, belts, and switches.

### Where to use:

- Schools and universities.
- Healthcare – acute and long term care.
- Office, commercial and industrial spaces.
- Retail stores, shopping malls, grocery stores.
- Government facilities.

### Specifications

Model	Ultron 20BA	Ultron 20TD
Item #	17021	17022
Productivity rate	19,375 ft <sup>2</sup> / hr	23,680 ft <sup>2</sup> / hr
Drive system	Brush Assisted	Transaxle, 0.27hp / 0.2KW
Travel speed, maximum	N/A	246 ft / min
Weight	210 lbs	230 lbs
Weight with batteries	410 lbs	440 lbs
Recovery tank capacity	17.2 gal	
Solution tank capacity	15.9 gal	
Squeegee width	30 in	
Floor pad size	20 in (Disk)	
Brush speed	220 RPM / min	
Wheel diameter	8 in	
Minimum aisle turn	63 in	
Pad / brush pressure	65 lbs / 100 lbs Max	
Solution flow rate	0 ~ 0.37 gal / min	
Brush motor	0.75 hp / 0.55 KW, 2,200 RPM	
Vacuum motor	0.7 hp / 0.5 KW	
Vacuum water lift	45 in H <sub>2</sub> O	
Batteries	Requires 2-12V (Available in Wet & AGM)	
Run time per charge	3.5 Hours	3 Hours
Voltage DC	24 V	
Decibel rate at operator's ear, indoors	68 dB(A)	
Grade level, max	5% (3°)	
Dimensions L x W x H	55.7 x 22 x 44.9 in	

Specifications are subject to change without notice.