



Panther 20TO

Orbital Automatic Scrubber



Panther 20TO Orbital Automatic Scrubber



Control panel with intuitive display



Water level indicator



Efficient orbital scrub deck for intensive cleaning or floor coat stripping

The Panther 20TO is a highly productive walk-behind automatic scrubber with battery and tank capacity to clean for hours. With a working width of 20 inches and a tank capacity of 16 gallons this scrubber will get the job done fast and easy. The Panther 20TO is well balanced and easy to maneuver thanks to large main wheels and strong supporting casters.

For intensive cleaning or maintaining large coated floor areas, the Panther 20TO with an orbital scrub deck ensures multi directional cleaning performance with low solution and detergent consumption, and the rectangular deck allows easy access to corners.

- High capacity 16-gallon solution and recovery tanks
- Onboard charger for convenient battery charging
- Safety switches built into the handle
- Disc version available with or without traction motor
- Orbital version offers water and detergent savings, with traction drive, and automatic raising and lowering of the scrub deck.

Where to use:

- Schools and universities.
- Healthcare - acute and long term care.
- Office, commercial and industrial spaces.
- Retail stores, shopping malls, grocery stores.
- Government facilities.

Specifications	
Model	Panther 20TO
Item #	86017
Productivity rate	23,680 sq ft/hr
Drive system	Power Traction
Travel speed maximum	2.8 mph
Weight	330 lbs
Weight with batteries	490 lbs
Recovery tank capacity	16 gal (61L)
Solution tank capacity	16 gal (61L)
Squeegee width	31 in (790 mm)
Cleaning path width	20 in (510mm)
Brush speed	2200 rpm
Wheel diameter	Front: 8 in / Rear: 3 in
Minimum aisle turn	56 in
Pad/brush pressure	88 -110 lbs (40 kg - 50 kg)
Solution flow rate	0 - .63 gal/min
Brush motor	.5 hp
Vaccum motor	.5 hp
Vaccum water lift	47 in (1,200 mm)
Batteries (required)	(2) 130 A/H Wet or (2) 140 A/H AGM
Run time per charge	2.5 hours
Voltage DC	24 Volt
Decibel rate at operator's Ear, indoors	69 +/- 3 dB(A)
Grade level, max	2%
Dimensions LxWxH	52 x 22 x 39 in

Specifications are subject to change without notice.